

Postel

Network Working Group  
Request for Comments #145  
NIC #6739  
Category: D.1  
Updates: #123  
Obsoletes: #127

J. Postel  
4 May 1971  
UCLA - NMC  
Computer Science

Initial Connection Protocol Control Commands

The following is my interpretation of the exchange between NCP's which would be necessary to carry out the Initial Connection Protocol of RFC #123. (This note corrects an error pointed out by Eric Harslem of RAND)

Server NCP

User NCP

Listen for Connection on L

RTS, U, L,  $l_A$

STR, L, U, 32

ALL,  $l_A$ , 1, 32

Send 32 bits of data  
in 1 message on link  $l_A$

Receive 32 bits of data  
from link  $l_A$  (value is S)

(value is S)

CLS, L, U  
STR, S+1, (U+1),  $B_S$

CLS, U, L  
STR, U+1, S,  $B_U$

RTS, S, U+1,  $l_B$

RTS, U, S+1,  $l_C$

wait for connection

wait for connection

ALL,  $l_B$ ,  $m_B$ ,  $b_B$

ALL,  $l_C$ ,  $m_C$ ,  $b_C$

data sent on link  $l_C$

data sent on link  $l_B$

data received on link  $l_B$

data received on link  $l_C$

$l_A$ ,  $l_B$ , and  $l_C$  are links,  $m_B$  and  $m_C$  are message allocations,  $b_B$  and  $b_C$  are bit allocations, and all other symbols are as defined in RFC #123.