

Network Working Group
Request for Comments: 4444
Category: Standards Track

J. Parker, Ed.
Axiowave Networks
April 2006

Management Information Base for
Intermediate System to Intermediate System (IS-IS)

Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Specifically, this document describes a MIB for the Intermediate System to Intermediate System (IS-IS) Routing protocol when it is used to construct routing tables for IP networks.

Table of Contents

1. The Internet-Standard Management Framework	2
2. Overview	2
3. Conventions	5
4. Definition of IS-IS MIB.	6
5. IANA Considerations.	96
6. Acknowledgements	96
7. Security Considerations.	96
8. Normative References	101
9. Informative References	102

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

2. Overview

This document describes a management information base for the Intermediate System to Intermediate System (IS-IS) Routing protocol, as described in ISO 10589 [ISO10589], when it is used to construct routing tables for IP networks, as described in RFC 1195 [RFC1195]. The objects are mainly derived from the Guidelines for Definition of Managed Objects (GDMO) definitions in ISO 10589 and from the GDMO definitions in ISO 10733 [ISO10733]. There are also additional objects for managing the IP-specific functionality of Integrated IS-IS operation.

This MIB imports definitions from SNMPv2-TC [RFC2579], SNMPv2-SMI [RFC2578], SNMPv2-CONF [RFC2580], SNMP-FRAMEWORK-MIB [RFC3411], DIFFSERV-MIB [RFC3289], IF-MIB [RFC2863], and INET-ADDRESS-MIB [RFC4001]. See the imports section of the MIB for the specific items imported.

This MIB defines some objects to manage Mesh Groups, described in [RFC2973], and a three-way handshake for point-to-point adjacencies, described in [RFC3373].

The IS-IS MIB defines the following objects:

System-Wide Attributes

- `isisSystem`

This table contains information specific to a single instance of the IS-IS protocol running on a router.

- **isisManAreaAddr**

This table includes area addresses that are manually configured, which are used to control the associations formed between Level 1 Intermediate Systems.

- **isisAreaAddr**

This table includes area addresses reported in relevant L1 LSPs.

- **isisSummAddr**

This table holds summary addresses configured for each Level 2 instance of the IS-IS protocol running on a router.

- **isisRedistributeAddr**

This table provides criteria to decide whether a route should be leaked from L2 to L1 when Domain Wide Prefix leaking is enabled.

- **isisRouter**

This table holds the hostname and router ID for Intermediate Systems in the network.

- **isisSysLevel**

This table contains information specific to a domain (Level 2) or an area (Level 1) of the IS-IS protocol.

- **isisNextCircIndex**

This scalar is used to provide a unique circuit index.

Circuit-specific Attributes

- **isisCirc**

This table contains information specific to a point-to-point or a broadcast interface in the system.

- **isisCircLevel**

This table contains information specific to Level 1 or Level 2 of an interface.

Counters

- `isisSystemCounter`

Counters in the System table, such as number of times we have wrapped a sequence counter on one of our Link State PDUs.

- `isisCircuitCounter`

Counters of events particular to a circuit, such as PDUs with an illegal value of the System ID field length.

- `isisPacketCounter`

Counts of IS-IS Protocol PDUs broken down into packet type.

Attributes associated with an Adjacency

- `isisISAdj`

This table contains information about adjacencies to routers maintained by the protocol. Entries in this table cannot be created by management action: they are established through the Hello protocol.

- `isisISAdjAreaAddr`

This table contains the set of Area Addresses of neighboring Intermediate Systems, as reported in IIH PDUs.

- `isisISAdjIPAddr`

This table contains the set of IP Addresses of neighboring Intermediate Systems, as reported in received IIH PDUs.

- `isisISAdjProtSupp`

This table contains the set of protocols supported by neighboring Intermediate Systems, as reported in received IIH PDUs.

Attributes Associated with Addresses

- **isisRA**

The Reachable Address Table.

This table contains information about an address prefix manually configured on the system or learned through another protocol.

- **isisIPRA**

The IP Reachable Address Table.

This table contains information about an IP reachable address manually configured on this system or learned from another protocol.

Attributes Associated with Link State PDU Table

- **isisLSPSummaryTable**

The Link State PDU Summary Table.

This table contains information contained in the headers of Link State PDUs stored by the system.

- **isisLSPTLVTable**

The Link State PDU TLV Table.

This table holds the sequence of TLVs that make up an LSP fragment.

Attributes Associated with a Notification

- **isisNotification**

This table defines attributes that will be included when reporting IS-IS notifications.

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL", when they appear in this document, are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

4. Definition of IS-IS MIB

```
ISIS-MIB DEFINITIONS ::= BEGIN
  IMPORTS
    TEXTUAL-CONVENTION, RowStatus, TruthValue, TimeStamp
      FROM SNMPv2-TC                                -- RFC2579
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
      Unsigned32, Counter32, mib-2
      FROM SNMPv2-SMI                               -- RFC2578
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
      FROM SNMPv2-CONF                             -- RFC2580
    SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB                      -- RFC2571
    IndexInteger, IndexIntegerNextFree
      FROM DIFFSERV-MIB                            -- RFC3289
    InterfaceIndex
      FROM IF-MIB                                 -- RFC2863
    InetAddressType, InetAddress, InetAddressPrefixLength
      FROM INET-ADDRESS-MIB;                      -- RFC3291

isisMIB MODULE-IDENTITY
LAST-UPDATED "200604040000Z" -- April 4, 2006, midnight
ORGANIZATION "IETF IS-IS for IP Internets Working Group"
CONTACT-INFO
  "IS-IS for IP Internets working Group
   http://www.ietf.org/html.charters/isis-charter.html
   isis-wg@ietf.org

  Jeff Parker
  Department of Computer Science
  Middlebury College,
  Middlebury, Vermont 05753
  jeffp at middlebury dot edu"

DESCRIPTION
  "This document describes a management information base for
   the IS-IS Routing protocol, as described in ISO 10589,
   when it is used to construct routing tables for IP
   networks, as described in RFC 1195.

  This document is based on a 1994 IETF document by Chris
  Gunner. This version has been modified to include
  current syntax, to exclude portions of the protocol that
  are not relevant to IP, and to add management support for
  current practice."
```

Copyright (C) The Internet Society (2006). This version of this MIB module is part of RFC 4444; see the RFC itself for full legal notices."

REVISION "200604040000Z" -- April 4, 2006, midnight

DESCRIPTION

"Initial version, published as RFC 4444."

::= { mib-2 138 }

-- Top-level structure of the MIB

isisNotifications OBJECT IDENTIFIER ::= { isisMIB 0 }
isisObjects OBJECT IDENTIFIER ::= { isisMIB 1 }
isisConformance OBJECT IDENTIFIER ::= { isisMIB 2 }

-- OBJECT IDENTIFIER definitions

-- System wide attributes.

isisSystem OBJECT IDENTIFIER ::= { isisObjects 1 }

-- Attributes associated with the domain or with the area.
isisSysLevel OBJECT IDENTIFIER ::= { isisObjects 2 }

-- Attributes associated with one Circuit

isisCirc OBJECT IDENTIFIER ::= { isisObjects 3 }

-- Attributes associated with area or domain relevant within a Circuit.
isisCircLevelValues OBJECT IDENTIFIER ::= { isisObjects 4 }

-- System and circuit counters.

isisCounters OBJECT IDENTIFIER ::= { isisObjects 5 }

-- Attributes associated with an adjacent Protocol Peer.

isisISAdj OBJECT IDENTIFIER ::= { isisObjects 6 }

-- Attributes associated with a configured address.

isisReachAddr OBJECT IDENTIFIER ::= { isisObjects 7 }

-- Attributes associated with IP routes learned by

-- configuration or through another protocol.

isisIPReachAddr OBJECT IDENTIFIER ::= { isisObjects 8 }

-- The collection of Link State PDUs known to the Intermediate System
isisLSPDataBase OBJECT IDENTIFIER ::= { isisObjects 9 }

-- Objects included in Notifications.

isisNotification OBJECT IDENTIFIER ::= { isisObjects 10 }

-- Type definitions

```

IsisOSINSAddress ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "OSI Network Service Address, e.g., NSAP, SNPA, or Network
         Entity Title"
    SYNTAX OCTET STRING (SIZE(0..20))

IsisSystemID ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The ID for an Intermediate System. This should
         be unique within a network, and is included
         in all PDUs originated by an Intermediate System.
         The protocol does not place any meanings upon
         the bits, other than using ordering to break
         ties in electing a Designated IS on a LAN."
    REFERENCE "{ISIS.aoi systemId (119)}"
    SYNTAX OCTET STRING (SIZE(6))

IsisLinkStatePDUID ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The 8-byte Link State PDU (LSP) ID,
         consisting of the 6-byte SystemID of the
         originating IS; a one-byte PseudoNode ID,
         which is 0 unless the LSP represents the
         topology of a LAN; and a one-byte LSP
         fragment number that is issued in sequence,
         starting with 0. Non-zero PseudoNode IDs
         need to be unique to the IS but need not
         match the IfIndex."
    REFERENCE "{See section 9.8 of ISO 10589}"
    SYNTAX OCTET STRING (SIZE(8))

IsisAdminState ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "Type used in enabling and disabling a row."
    SYNTAX INTEGER
    {
        on(1),
        off(2)
    }

IsisLSPBuffSize ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"

```

```
STATUS current
DESCRIPTION
  "Integer sub-range for maximum LSP size."
SYNTAX Unsigned32 (512..16000)

IsisLevelState ::= TEXTUAL-CONVENTION
  STATUS current
  DESCRIPTION
    "States of the IS-IS protocol."
  SYNTAX INTEGER
  {
    off (1),
    on (2),
    waiting (3),
    overloaded(4)
  }

IsisSupportedProtocol ::= TEXTUAL-CONVENTION
  STATUS current
  DESCRIPTION
    "Types of network protocol supported by Integrated IS-IS.
     The values for ISO8473 and IP are those registered for
     these protocols in ISO TR9577."
  REFERENCE "{See section 5.3.1 of RFC 1195}"
  SYNTAX INTEGER
  {
    iso8473(129),
    ipV6(142),
    ip(204)
  }

IsisDefaultMetric ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS current
  DESCRIPTION
    "Integer sub-range for default metric for single hop.
     ISO 10589 provides for 4 types of metric. Only the
     'default' metric is used in practice."
  REFERENCE "{See section 7.2.2 of ISO 10589}"
  SYNTAX Unsigned32 (0..63)

IsisWideMetric ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS current
  DESCRIPTION
    "Wide metric for IS Neighbors. ISO 10589 provides a
     6-bit metric. Traffic Engineering extensions provide
     24-bit metrics."
```

```
REFERENCE "{See section 3 of RFC 3784}"
SYNTAX Unsigned32 (0..16777215)

IsisFullMetric ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS current
DESCRIPTION
  "Full metric for IP Routes. Traffic Engineering extensions
   provide 32-bit metrics."
REFERENCE "{See section 4 of RFC 3784}"
SYNTAX Unsigned32

IsisMetricType ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
  "Is this an Internal or External Metric?"
REFERENCE "{See section 7.2.2 of ISO 10589}"
SYNTAX INTEGER
{
  internal(1),
  external(2)
}

IsisMetricStyle ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
  "Do we use RFC 1195 style metrics or wide metrics?"
REFERENCE "{See section 5 of RFC 3787}"
SYNTAX INTEGER
{
  narrow(1),
  wide(2),
  both(3)
}

IsisISLevel ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
  "Identifies a level."
REFERENCE "{See definitions 3.6.1 and 3.6.11 of ISO 10589}"
SYNTAX INTEGER
{
  area(1),          -- L1
  domain(2)         -- L2
}

IsisLevel ::= TEXTUAL-CONVENTION
STATUS current
```

```
DESCRIPTION
    "Identifies one or more levels."
REFERENCE "{See definitions 3.6.1 and 3.6.11 of ISO 10589}"
SYNTAX INTEGER
{
    level1(1),
    level2(2),
    level1and2(3)
}

IsisPDUHeader ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
    "A block to contain the header from a PDU."
SYNTAX OCTET STRING (SIZE(0..64))

IsisCircuitID ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
    "ID for a circuit."
REFERENCE "{See section 7.2.7 of ISO 10589}"
SYNTAX OCTET STRING (SIZE(0|7))

IsisISPRIORITY ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS current
DESCRIPTION
    "Integer sub-range for IS-IS priority."
REFERENCE "{See section 9.5 of ISO 10589}"
SYNTAX Unsigned32 (0..127)

IsisUnsigned16TC ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS current
DESCRIPTION
    "An Unsigned32 further restricted to 16 bits. Note that
     the ASN.1 BER encoding may still require 24 bits for
     some values."
SYNTAX Unsigned32 (0..65535)

IsisUnsigned8TC ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS current
DESCRIPTION
    "An Unsigned32 further restricted to 8 bits. Note that
     the ASN.1 BER encoding may still require 16 bits for
     some values."
SYNTAX Unsigned32 (0..255)
```

```
-- Behavior Definitions

-- ResettingTimer behavior definition
--

-- "This behavior applies to objects that specify the interval
-- between events in the operation of the protocol state machine.
-- If the value of such an object is set to a new value while
-- the protocol state machine is in operation, the implementation
-- shall take the necessary steps to ensure that for any time
-- interval that was in progress when the value of the
-- corresponding object was changed, the next expiration of that
-- interval takes place the specified time after the original
-- start of that interval, or immediately, whichever is later.
-- The precision with which this time shall be implemented shall
-- be the same as that associated with the basic operation of
-- the timer object."

-- ReplaceOnlyWhileDisabled behavior definition
-- "This behavior applies to objects that may not be modified
-- while the corresponding table row's variable of type
-- IsisAdminState is in state on."

-- ManualOrAutomatic behavior definition
-- "This behavior applies to objects that are read-write
-- if the object was created manually. Objects that were
-- created automatically that have this behavior are
-- read-only.

isisSysObject OBJECT IDENTIFIER ::= { isisSystem 1 }

isisSysVersion OBJECT-TYPE
    SYNTAX INTEGER
    {
        unknown(0),
        one(1)
    }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The version number of the IS-IS protocol that
         is implemented."
    REFERENCE "{ISIS.aoi version (1)}"
    DEFVAL { one }
    ::= { isisSysObject 1 }

isisSysLevelType OBJECT-TYPE
    SYNTAX IsisLevel
```

```
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "At which levels is the Intermediate System
   running? This object may not be modified when
   the isisSysAdminState variable is in state 'on'
   for this Intermediate System.

  Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi iSType (2)}"
DEFVAL { level1and2 }
::= { isisSysObject 2 }

isisSysID OBJECT-TYPE
SYNTAX IsisSystemID
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "The ID for this Intermediate System.
   This value is appended to each of the
   area addresses to form the Network Entity Titles.
   The derivation of a value for this object is
   implementation specific. Some implementations may
   automatically assign values and not permit an
   SNMP write, while others may require the value
   to be set manually.

  Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi systemId (119)}"
::= { isisSysObject 3 }

isisSysMaxPathSplits OBJECT-TYPE
SYNTAX Unsigned32 (1..32)
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "Maximum number of paths with equal routing metric value
   which it is permitted to split between. This object
   may not be modified when the isisSysAdminState variable
   is in state 'on' for this Intermediate System.

  Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi maximumPathSplits (3)}"
DEFVAL { 2 }
::= { isisSysObject 4 }

isisSysMaxLSPGenInt OBJECT-TYPE
SYNTAX Unsigned32 (1..65235)
```

```

UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "Maximum interval, in seconds, between generated LSPs
  by this Intermediate System. This object follows
  the ResettingTimer behavior. The value must be
  greater than any value configured for
  isisSysLevelMinLSPGenInt, and should be at least 300
  seconds less than isisSysMaxAge.

  Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi maximumLSPGenerationInterval (6)}"
DEFVAL { 900 }
 ::= { isisSysObject 5 }

isisSysPollESHelloRate OBJECT-TYPE
  SYNTAX IsisUnsigned16TC (1..65535)
  UNITS "seconds"
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "The value, in seconds, to be used for the suggested ES
     configuration timer in ISH PDUs when soliciting the ES
     configuration.

    Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi pollESHelloRate (13)}"
DEFVAL { 50 }
 ::= { isisSysObject 6 }

isisSysWaitTime OBJECT-TYPE
  SYNTAX IsisUnsigned16TC (1..65535)
  UNITS "seconds"
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "Number of seconds to delay in state 'waiting' before
     entering the state 'on'. This object follows the
     ResettingTimer behavior.

    Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi waitingTime (15)}"
DEFVAL { 60 }
 ::= { isisSysObject 7 }

isisSysAdminState OBJECT-TYPE
  SYNTAX IsisAdminState

```

```
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "The administrative state of this Intermediate
  System. Setting this object to the value 'on'
  when its current value is 'off' enables
  the Intermediate System.

  Configured values MUST survive an agent reboot."
  DEFVAL { off }
  ::= { isisSysObject 8 }

isisSysL2toL1Leaking OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "If true, allow the router to leak L2 routes into L1.

  Configured values MUST survive an agent reboot."
  DEFVAL { false }
  ::= { isisSysObject 9 }

isisSysMaxAge OBJECT-TYPE
SYNTAX IsisUnsigned16TC (350..65535)
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "Value to place in RemainingLifeTime field of
  the LSPs we generate.
  This should be at least 300 seconds greater than
  isisSysMaxLSPGenInt.

  Configured values MUST survive an agent reboot."
  DEFVAL { 1200 }
  ::= { isisSysObject 10 }

isisSysReceiveLSPBufferSize OBJECT-TYPE
SYNTAX IsisUnsigned16TC (1492..16000)
UNITS "bytes"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "Size of the largest buffer we are designed or
  configured to store. This should be at least
  as big as the maximum isisSysLevelOrigLSPBuffSize
  supported by the system.
```

If resources allow, we will store and flood LSPs larger than isisSysReceiveLSPBufferSize, as this can help avoid problems in networks with different values for isisSysLevelOrigLSPBuffSize.

Configured values MUST survive an agent reboot."

DEFVAL { 1492 }
 ::= { isisSysObject 11 }

isisSysProtSupported OBJECT-TYPE
 SYNTAX BITS {
 iso8473 (0),
 ipv4 (1),
 ipv6 (2)
 }
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "This attribute contains the set of protocols supported by this Intermediate System."
 ::= { isisSysObject 12 }

isisSysNotificationEnable OBJECT-TYPE
 SYNTAX TruthValue
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "If this object is set to true(1), then it enables the emission of IS-IS Notifications. If it is set to false(2), these notifications are not sent.
 Configured values MUST survive an agent reboot."
 DEFVAL { true }
 ::= { isisSysObject 13 }

-- The Level 1 Manual Area Address Table

isisManAreaAddrTable OBJECT-TYPE
 SYNTAX SEQUENCE OF IsisManAreaAddrEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "The set of manual area addresses configured on this Intermediate System.

At least one row in which the value of isisManAreaAddrExistState is active must be present.
 The maximum number of rows in this table for

which the object `isisManAreaAddrExistState` has the value `active` is 3.

An attempt to create more than 3 rows of `isisManAreaAddrEntry` with state 'active' in one instance of the IS-IS protocol should return `inconsistentValue`."

REFERENCE "{`ISIS.aoi manualAreaAddresses (10)`}"
`::= { isisSystem 2 }`

`isisManAreaAddrEntry` OBJECT-TYPE
 SYNTAX `IsisManAreaAddrEntry`
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "Each entry contains one area address manually configured on this system.

Dynamically created rows MUST survive an agent reboot."
 INDEX { `isisManAreaAddr` }
`::= { isisManAreaAddrTable 1 }`

`IsisManAreaAddrEntry` ::=
 SEQUENCE {
 `isisManAreaAddr`
 `IsisOSINSAddress`,
 `isisManAreaAddrExistState`
 `RowStatus`
 }

`isisManAreaAddr` OBJECT-TYPE
 SYNTAX `IsisOSINSAddress`
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "A manually configured area address for this system.

Note: An index for the entry {1, {49.0001} active} in this table would be the ordered pair (1, (0x03 0x49 0x00 0x01)), as the length of an octet string is part of the OID."
`::= { isisManAreaAddrEntry 1 }`

`isisManAreaAddrExistState` OBJECT-TYPE
 SYNTAX `RowStatus`
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION

"The state of the isisManAreaAddrEntry. If the isisSysAdminState for this Intermediate System is 'on' and an attempt is made to set this object to the value 'destroy' or 'notInService' when this is the only isisManAreaAddrEntry in state 'active' for this Intermediate System should return inconsistentValue.

A row entry cannot be modified when the value of this object is 'active'."

::= { isisManAreaAddrEntry 2 }

-- The Level 1 Area Address Table

-- The Level 1 Area Address Table contains the
-- union of the sets of relevant area addresses configured
-- or learned from Level 1 LSPs received by this Intermediate System.

isisAreaAddrTable OBJECT-TYPE
 SYNTAX SEQUENCE OF IsisAreaAddrEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "The union of the sets of area addresses reported in all
 Level 1 LSPs with fragment number zero generated by this
 Intermediate System, or received from other Intermediate
 Systems that are reachable via Level 1 routing."
 REFERENCE "{ISIS.aoi areaAddresses (18)}"
 ::= { isisSystem 3 }

isisAreaAddrEntry OBJECT-TYPE
 SYNTAX IsisAreaAddrEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "Each entry contains one area address reported in a
 Level 1 LSP generated or received by this Intermediate
 System."

Dynamically learned rows do not survive an agent reboot."
 INDEX { isisAreaAddr }
 ::= { isisAreaAddrTable 1 }

IsisAreaAddrEntry ::=
 SEQUENCE {
 isisAreaAddr
 IsisOSINSAddress
 }

```
isisAreaAddr OBJECT-TYPE
  SYNTAX IsisOSINSAddress
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "An area address reported in a Level 1 LSP."
 ::= { isisAreaAddrEntry 1 }

-- The Summary Address Table

-- The Summary Address Table contains the set of summary
-- addresses manually configured for the Intermediate System.
--
-- This is used to control leaking L1 routes into L2.

isisSummAddrTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisSummAddrEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The set of IP summary addresses to use in forming
     summary TLVs originated by this Intermediate System.

    An administrator may use a summary address to combine
    and modify IP Reachability announcements. If the
    Intermediate system can reach any subset of the summary
    address, the summary address MUST be announced instead,
    at the configured metric."
 ::= { isisSystem 4 }

isisSummAddrEntry OBJECT-TYPE
  SYNTAX IsisSummAddrEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry contains one IP summary address.

    Dynamically created rows MUST survive an agent reboot.

    Implementers need to be aware that if the total number
    of elements (octets or sub-identifiers) in
    isisSummAddress and isisSummAddrPrefixLen is too great,
    then OIDs of column instances in this table will have
    more than 128 subidentifiers and cannot be accessed
    using SNMPv1, SNMPv2c, or SNMPv3.

INDEX { isisSummAddressType,
        isisSummAddress,
        isisSummAddrPrefixLen }
```

```

 ::= { isisSummAddrTable 1 }

IsisSummAddrEntry ::= 
SEQUENCE {
    isisSummAddressType
        InetAddressType,
    isisSummAddress
        InetAddress,
    isisSummAddrPrefixLen
        InetAddressPrefixLength,
    isisSummAddrExistState
        RowStatus,
    isisSummAddrMetric
        IsisDefaultMetric,
    isisSummAddrFullMetric
        IsisFullMetric
}
}

isisSummAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The Type of IP address for this summary address."
 ::= { isisSummAddrEntry 1 }

isisSummAddress OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The IP Address value for this summary address.
The address must not contain any set host bits
(bits set after the address prefix determined by
isisSummAddrPrefixLen).

The type of this address is determined by the value of
the isisSummAddressType object."
 ::= { isisSummAddrEntry 2 }

isisSummAddrPrefixLen OBJECT-TYPE
SYNTAX InetAddressPrefixLength
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The Length of the IP NetMask for this summary address.

The values for the index objects isisSummAddress and

```

isisSummAddrPrefixLen must be consistent. When the value of isisSummAddress (excluding the zone index, if one is present) is x , then the bitwise logical-AND of x with the value of the mask formed from the corresponding index object isisSummAddrPrefixLen MUST be equal to x . If not, then the index pair is not consistent, and an inconsistentName error must be returned on SET or CREATE requests."

```
::= { isisSummAddrEntry 3 }
```

isisSummAddrExistState OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The existence state of this summary address. Support for 'createAndWait' and 'notInService' is not required.

A row entry cannot be modified when the value of this object is 'active'."

```
::= { isisSummAddrEntry 4 }
```

isisSummAddrMetric OBJECT-TYPE

SYNTAX IsisDefaultMetric

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The metric value to announce this summary address within LSPs generated by this system."

DEFVAL { 20 }

```
::= { isisSummAddrEntry 5 }
```

isisSummAddrFullMetric OBJECT-TYPE

SYNTAX IsisFullMetric

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The wide metric value to announce this summary address within LSPs generated by this system."

DEFVAL { 20 }

```
::= { isisSummAddrEntry 6 }
```

-- The Redistribution table defines addresses that should be leaked from L2 to L1 if isisSysL2toL1Leaking is enabled.

isisRedistributeAddrTable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisRedistributeAddrEntry

MAX-ACCESS not-accessible

```

STATUS current
DESCRIPTION
"This table provides criteria to decide if a route should
be leaked from L2 to L1 when Domain Wide Prefix leaking is
enabled.

Addresses that match the summary mask in the table MUST
be announced at L1 by routers when isisSysL2toL1Leaking
is enabled. Routes that fall into the ranges specified
are announced as is, without being summarized. Routes
that do not match a summary mask are not announced."
 ::= { isisSystem 5 }

isisRedistributeAddrEntry OBJECT-TYPE
SYNTAX IsisRedistributeAddrEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Each entry contains one configured IP summary
address to manage leaking L2 addresses into L1.

Dynamically created rows MUST survive an agent reboot.

Implementers need to be aware that if the total number
of elements (octets or sub-identifiers) in
isisRedistributeAddrAddress and
isisRedistributeAddrPrefixLen is too great, then OIDs
of column instances in this table will have more than
128 subidentifiers and cannot be accessed using SNMPv1,
SNMPv2c, or SNMPv3."
INDEX { isisRedistributeAddrType,
        isisRedistributeAddrAddress,
        isisRedistributeAddrPrefixLen }
 ::= { isisRedistributeAddrTable 1 }

IsisRedistributeAddrEntry ::=
SEQUENCE {
    isisRedistributeAddrType
        InetAddressType,
    isisRedistributeAddrAddress
        InetAddress,
    isisRedistributeAddrPrefixLen
        InetAddressPrefixLength,
    isisRedistributeAddrExistState
        RowStatus
}
isisRedistributeAddrType OBJECT-TYPE

```

```
SYNTAX InetAddressType
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "The Type of IP address for this summary address."
::= { isisRedistributeAddrEntry 1 }

isisRedistributeAddrAddress OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The IP Address value for this summary address.
        The type of this address is determined by the
        value of the isisRedistributeAddrType object.
        The address must not contain any set host bits -
        bits set after the address prefix determined by
        isisRedistributeAddrPrefixLen."
::= { isisRedistributeAddrEntry 2 }

isisRedistributeAddrPrefixLen OBJECT-TYPE
    SYNTAX InetAddressPrefixLength
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The Length of the IP NetMask for this summary address.

        The values for the index objects
        isisRedistributeAddrAddress and
        isisRedistributeAddrPrefixLen must be consistent.
        When the value of isisRedistributeAddrAddress
        (excluding the zone index, if one is present) is x,
        then the bitwise logical-AND of x with the value of
        the mask formed from the corresponding index object
        isisRedistributeAddrPrefixLen MUST be equal to x.
        If not, then the index pair is not consistent, and an
        inconsistentName error must be returned on SET or
        CREATE requests."
::= { isisRedistributeAddrEntry 3 }

isisRedistributeAddrExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The existence state of this summary address.  Support
```

for createAndWait and notInService is not required.

A row entry cannot be modified when the value of this object is 'active'."

::= { isisRedistributeAddrEntry 4 }

-- The Router Table keeps track of hostnames and router IDs
-- associated with Intermediate Systems in the area and domain.

isisRouterTable OBJECT-TYPE
SYNTAX SEQUENCE OF IsisRouterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The set of hostnames and router ID."
 ::= { isisSystem 6 }

isisRouterEntry OBJECT-TYPE
SYNTAX IsisRouterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Each entry tracks information about one Intermediate System at one level.

Dynamically learned rows do not survive an agent reboot."

INDEX { isisRouterSysID,
isisRouterLevel }

::= { isisRouterTable 1 }

IsisRouterEntry ::=
SEQUENCE {
isisRouterSysID
IsisSystemID,
isisRouterLevel
IsisISLevel,
isisRouterHostName
SnmpAdminString,
isisRouterID
Unsigned32
}

isisRouterSysID OBJECT-TYPE
SYNTAX IsisSystemID
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The System ID of the Intermediate System."

```
 ::= { isisRouterEntry 1 }

isisRouterLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level at which the information about this
         Intermediate System was received."
 ::= { isisRouterEntry 2 }

isisRouterHostName OBJECT-TYPE
    SYNTAX SnmpAdminString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The hostname listed in the LSP, or a zero-length
         string if none."
 ::= { isisRouterEntry 3 }

isisRouterID OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The Router ID found in the LSP, or zero if none."
 ::= { isisRouterEntry 4 }

-- The System Level Table
-- This table captures level-specific information about the system

isisSysLevelTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisSysLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Level specific information about the System."
 ::= { isisSysLevel 1 }

isisSysLevelEntry OBJECT-TYPE
    SYNTAX IsisSysLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each row describes variables configured for Area or Domain.

         Configured values MUST survive an agent reboot."
 INDEX { isisSysLevelIndex }
```

```
::= { isisSysLevelTable 1 }

IsisSysLevelEntry ::= SEQUENCE {
    isisSysLevelIndex
        IsisISLevel,
    isisSysLevelOrigLSPBuffSize
        IsisLSPBuffSize,
    isisSysLevelMinLSPGenInt
        IsisUnsigned16TC,
    isisSysLevelState
        IsisLevelState,
    isisSysLevelSetOverload
        TruthValue,
    isisSysLevelSetOverloadUntil
        Unsigned32,
    isisSysLevelMetricStyle
        IsisMetricStyle,
    isisSysLevelSPFConsiders
        IsisMetricStyle,
    isisSysLevelTEEnabled
        TruthValue
}

isisSysLevelIndex OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level that this entry describes."
:={ isisSysLevelEntry 1 }

isisSysLevelOrigLSPBuffSize OBJECT-TYPE
    SYNTAX IsisLSPBuffSize
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The maximum size of LSPs and SNPs originated by
        this Intermediate System at this level. This
        object may not be modified when the isisSysAdminState
        variable is in state 'on' for this Intermediate System."
    REFERENCE "{ISIS.aoi originatingL1LSPBufferSize (9)}"
    DEFVAL { 1492 }
:={ isisSysLevelEntry 2 }

isisSysLevelMinLSPGenInt OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (1..65535)
    UNITS "seconds"
```

```

MAX-ACCESS read-write
STATUS current
DESCRIPTION
  "Minimum interval, in seconds, between successive
  generation of LSPs with the same LSPID at this level
  by this Intermediate System."
REFERENCE "{ISIS.aoi minimumLSPGenerationInterval (11)}"
DEFVAL { 30 }
::= { isisSysLevelEntry 3 }

isisSysLevelState OBJECT-TYPE
  SYNTAX IsisLevelState
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The state of the database at this level.
     The value 'off' indicates that IS-IS is not active at
     this level.
     The value 'on' indicates that IS-IS is active at this
     level and is not overloaded.
     The value 'waiting' indicates a database that is low on
     an essential resource, such as memory.
     The administrator may force the state to 'overloaded'
     by setting the object isisSysLevelSetOverload.
     If the state is 'waiting' or 'overloaded', we
     originate LSPs with the overload bit set."
REFERENCE "{ISIS.aoi llState (17)}"
::= { isisSysLevelEntry 4 }

isisSysLevelSetOverload OBJECT-TYPE
  SYNTAX TruthValue
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "Administratively set the overload bit for the level.
     The overload bit MUST continue to be set if the
     implementation runs out of memory, independent of
     this variable. It may also be set manually independent
     of this variable, using the isisSysLevelSetOverloadUntil
     object."
DEFVAL { false }
::= { isisSysLevelEntry 5 }

isisSysLevelSetOverloadUntil OBJECT-TYPE
  SYNTAX Unsigned32
  UNITS "Seconds until clearing manually set Overload Bit"
  MAX-ACCESS read-write
  STATUS current

```

DESCRIPTION

"If this object is non-zero, the overload bit is set at this level when the isisSysAdminState variable goes to state 'on' for this Intermediate System. The overload bit remains set for isisSysLevelSetOverloadUntil seconds. When isisSysLevelSetOverloadUntil seconds have elapsed, the overload flag remains set if the implementation has run out of memory, or if it is set manually using the isisSysLevelSetOverload object.

If isisSysLevelSetOverload is false, the system clears the overload bit when isisSysLevelSetOverloadUntil seconds have elapsed, if the system has not run out of memory."

```
::= { isisSysLevelEntry 6 }
```

isisSysLevelMetricStyle OBJECT-TYPE

SYNTAX IsisMetricStyle

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Which style of metric do we generate in our LSPs at this level?"

DEFVAL { narrow }

```
::= { isisSysLevelEntry 7 }
```

isisSysLevelSPFConsiders OBJECT-TYPE

SYNTAX IsisMetricStyle

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Which style of metric do we consider in our SPF computation at this level?"

DEFVAL { narrow }

```
::= { isisSysLevelEntry 8 }
```

isisSysLevelTEEnabled OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Do we do Traffic Engineering at this level?"

DEFVAL { false }

```
::= { isisSysLevelEntry 9 }
```

-- Static to provide next CircIndex

isisNextCircIndex OBJECT-TYPE

SYNTAX IndexIntegerNextFree

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "This object is used to assist a management
  application in creating new rows in the
  isisCircTable. If it is possible to create
  a new instance of isisCircEntry, then this
  object will contain a non-zero value that
  is not in use as the index of any row in the
  isisCircTable. The network manager reads the
  value of this object and then (if the
  value read is non-zero) attempts to create
  the corresponding instance of isisCircEntry.
  If the set request fails with the code
  'inconsistentValue', then the process must be
  repeated; if the set request succeeds, then
  the agent will change the value of this object
  according to an implementation-specific
  algorithm."
::= { isisCirc 1 }
```

```
-- The Circuit Table
-- Each broadcast or point-to-point interface on the system
-- corresponds to one entry in the Circuit table. However, there
-- may be multiple X.25 DA circuit entries in the Circuit table
-- for a given X.25 interface.
```

```
isisCircTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisCircEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The table of circuits used by this
     Intermediate System."
::= { isisCirc 2 }
```

```
isisCircEntry OBJECT-TYPE
  SYNTAX IsisCircEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An isisCircEntry exists for each circuit configured
     for Integrated IS-IS on this system.
```

```
  Dynamically created rows MUST survive an agent reboot."
INDEX { isisCircIndex }
::= { isisCircTable 1 }
```

```

IsisCircEntry ::=

SEQUENCE {
    isisCircIndex
        IndexInteger,
    isisCircIfIndex
        InterfaceIndex,
    isisCircAdminState
        IsisAdminState,
    isisCircExistState
        RowStatus,
    isisCircType
        INTEGER,
    isisCircExtDomain
        TruthValue,
    isisCircLevelType
        IsisLevel,
    isisCircPassiveCircuit
        TruthValue,
    isisCircMeshGroupEnabled
        INTEGER,
    isisCircMeshGroup
        Unsigned32,
    isisCircSmallHellos
        TruthValue,
    isisCircLastUpTime
        TimeStamp,
    isisCirc3WayEnabled
        TruthValue,
    isisCircExtendedCircID
        Unsigned32
}

isisCircIndex OBJECT-TYPE
    SYNTAX IndexInteger
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An index used to uniquely identify this circuit.
        When creating a row in this table, the
        isisNextCircIndex object should be retrieved,
        and its value should be specified as the value
        of this index using a SET operation. A retrieved
        value of zero(0) indicates that no rows can be
        created at this time."
::= { isisCircEntry 1 }

isisCircIfIndex OBJECT-TYPE
    SYNTAX InterfaceIndex

```

```
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The value of ifIndex for the interface to which this
     circuit corresponds. This object cannot be modified
     after creation."
::= { isisCircEntry 2 }

isisCircAdminState OBJECT-TYPE
    SYNTAX IsisAdminState
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The administrative state of the circuit."
    DEFVAL { off }
::= { isisCircEntry 3 }

isisCircExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The existence state of this circuit. Setting the state
         to 'notInService' halts the generation and processing of
         IS-IS protocol PDUs on this circuit. Setting the state
         to destroy will also erase any configuration associated
         with the circuit. Support for 'createAndWait' and
         'notInService' is not required.

        A row entry cannot be modified when the value of this
        object is 'active'."
::= { isisCircEntry 4 }

isisCircType OBJECT-TYPE
    SYNTAX INTEGER
    {
        broadcast(1),
        ptToPt(2),
        staticIn(3),
        staticOut(4),
        dA(5)
    }
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The type of the circuit. This object follows the
         ReplaceOnlyWhileDisabled behavior. The type specified
         must be compatible with the type of the interface defined
```

```

    by the value of isisCircIfIndex."
    REFERENCE "{ISIS.aoi type (33)}"
::= { isisCircEntry 5 }

isisCircExtDomain OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "If true, suppress normal transmission of and
        interpretation of Intra-domain IS-IS PDUs on this
        circuit."
    REFERENCE "{ISIS.aoi externalDomain (46)}"
    DEFVAL { false }
::= { isisCircEntry 6 }

isisCircLevelType OBJECT-TYPE
    SYNTAX IsisLevel
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Indicates which type of packets will be sent and
        accepted on this circuit. The values set will be
        saved, but the values used will be modified by
        the settings of isisSysLevelType. Thus, if the
        isisSysTpe is level2 and the isisCircLevelType
        for a circuit is level1, the circuit will not send
        or receive IS-IS packets. This object follows the
        ReplaceOnlyWhileDisabled behavior."
    DEFVAL { level1and2 }
::= { isisCircEntry 7 }

isisCircPassiveCircuit OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Should we include this interface in LSPs, even if
        it is not running the IS-IS Protocol?"
    DEFVAL { false }
::= { isisCircEntry 8 }

isisCircMeshGroupEnabled OBJECT-TYPE
    SYNTAX INTEGER
    {
        inactive(1),
        blocked(2),
        set(3)
    }

```

```

        }

MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "Is this port a member of a mesh group, or is it
  blocked? Circuits in the same mesh group act as a
  virtual multiaccess network. LSPs seen on one circuit
  in a mesh group will not be flooded to another circuit
  in the same mesh group."
REFERENCE "{ RFC 2973 }"
DEFVAL { inactive }
::= { isisCircEntry 9 }

isisCircMeshGroup OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "Circuits in the same mesh group act as a virtual
  multiaccess network. LSPs seen on one circuit in
  a mesh group will not be flooded to another circuit
  in the same mesh group. If isisCircMeshGroupEnabled
  is inactive or blocked, this value is ignored."
REFERENCE "{ RFC 2973 }"
::= { isisCircEntry 10 }

isisCircSmallHellos OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "Can we send unpadded hellos on LAN circuits? False
  means the LAN Hellos must be padded.
  Implementations should allow the administrator to read
  this value. An implementation need not be able to
  support unpadded hellos to be conformant."
DEFVAL { false }
::= { isisCircEntry 11 }

isisCircLastUpTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "How long the circuit has been enabled, measured in
  hundredths of seconds since the last re-initialization
  of the network management subsystem; 0 if the
  circuit has never been 'on'."
```

```

 ::= { isisCircEntry 12 }

isisCirc3WayEnabled OBJECT-TYPE
  SYNTAX TruthValue
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "Is this circuit enabled to run 3Way handshake?"
  DEFVAL { true }
 ::= { isisCircEntry 13 }

isisCircExtendedCircID OBJECT-TYPE
  SYNTAX Unsigned32
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The value to be used as the extended circuit ID in
     3Way handshake. This value is only used if
     isisCirc3WayEnabled is true, and it must be unique
     across all circuits on this IS."
 ::= { isisCircEntry 14 }

-- The Circuit Level Table
-- This table captures level-specific information about a circuit

isisCircLevelTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisCircLevelEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Level specific information about circuits used by IS-IS."
 ::= { isisCircLevelValues 1 }

isisCircLevelEntry OBJECT-TYPE
  SYNTAX IsisCircLevelEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An isisCircLevelEntry exists for each level on
     each circuit configured for Integrated IS-IS on
     this system.

     Configured values MUST survive an agent reboot."
  INDEX { isisCircIndex,
          isisCircLevelIndex }
 ::= { isisCircLevelTable 1 }

IsisCircLevelEntry ::=
```

```

SEQUENCE {
    isisCircLevelIndex
        IsisISLevel,
    isisCircLevelMetric
        IsisDefaultMetric,
    isisCircLevelWideMetric
        IsisWideMetric,
    isisCircLevelISPRIORITY
        IsisISPRIORITY,
    isisCircLevelIDOctet
        Unsigned32,
    isisCircLevelID
        IsisCircuitID,
    isisCircLevelDesIS
        IsisCircuitID,
    isisCircLevelHelloMultiplier
        Unsigned32,
    isisCircLevelHelloTimer
        Unsigned32,
    isisCircLevelDRHelloTimer
        Unsigned32,
    isisCircLevelLSPThrottle
        IsisUnsigned16TC,
    isisCircLevelMinLSPRetransInt
        Unsigned32,
    isisCircLevelCSNPInterval
        Unsigned32,
    isisCircLevelPartSNPInterval
        Unsigned32
}

```

```

isisCircLevelIndex OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level that this entry describes."
::= { isisCircLevelEntry 1 }

```

```

isisCircLevelMetric OBJECT-TYPE
    SYNTAX IsisDefaultMetric
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The metric value of this circuit for this level."
    REFERENCE "{ISIS.aoi_l1DefaultMetric (35)}"
    DEFVAL { 10 }
::= { isisCircLevelEntry 2 }

```

```

isisCircLevelWideMetric OBJECT-TYPE
  SYNTAX IsisWideMetric
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "The wide metric value of this circuit for this level."
  DEFVAL { 10 }
 ::= { isisCircLevelEntry 3 }

isisCircLevelISPRIORITY OBJECT-TYPE
  SYNTAX IsisISPRIORITY
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "The priority for becoming the LAN-Designated
     Intermediate System at this level."
  REFERENCE "{ISIS.aoi 12IntermediateSystemPriority (73)}"
  DEFVAL { 64 }
 ::= { isisCircLevelEntry 4 }

isisCircLevelIDOctet OBJECT-TYPE
  SYNTAX Unsigned32(0..255)
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "A one-byte identifier for the circuit selected by the
     Intermediate System.

On point-to-point circuits, the value is used as the Local
Circuit ID in point-to-point IIH PDUs transmitted on this
circuit. In this case, values of isisCircLevelIDOctet do
not need to be unique.

For broadcast circuits, the value is used to generate the
LAN ID that will be used if this Intermediate System is
elected as the Designated IS on this circuit. The value
is required to differ on LANs where the Intermediate System
is the Designated Intermediate System."
 ::= { isisCircLevelEntry 5 }

isisCircLevelID OBJECT-TYPE
  SYNTAX IsisCircuitID
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "On a point-to-point circuit with a fully initialized
     adjacency to a peer IS, the value of this object is
     the circuit ID negotiated during adjacency initialization.

```

On a point to point circuit without such an adjacency, the value is the concatenation of the local system ID and the one-byte isisCircLevelIDOctet for this circuit, i.e., the value that would be proposed for the circuit ID. On other circuit types, the value returned is the zero-length OCTET STRING."

REFERENCE "{ISIS.aoi ptPtCircuitID (51)}"
 ::= { isisCircLevelEntry 6 }

isisCircLevelDesIS OBJECT-TYPE
 SYNTAX IsisCircuitID
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The ID of the LAN-Designated Intermediate System on this circuit at this level. If, for any reason, this system is not partaking in the relevant Designated Intermediate System election process, then the value returned is the zero-length OCTET STRING."
 REFERENCE "{ISIS.aoi l2DesignatedIntermediateSystem (75)}"
 ::= { isisCircLevelEntry 7 }

isisCircLevelHelloMultiplier OBJECT-TYPE
 SYNTAX Unsigned32 (2..100)
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "This value is multiplied by the corresponding HelloTimer, and the result in seconds (rounded up) is used as the holding time in transmitted hellos, to be used by receivers of hello packets from this IS."
 REFERENCE "{ISIS.aoi isISHelloTimer (45)}"
 DEFVAL { 10 }
 ::= { isisCircLevelEntry 8 }

isisCircLevelHelloTimer OBJECT-TYPE
 SYNTAX Unsigned32 (10..600000)
 UNITS "milliseconds"
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "Maximum period, in milliseconds, between IIH PDUs on multiaccess networks at this level for LANs. The value at L1 is used as the period between Hellos on L1L2 point-to-point circuits. Setting this value at level 2 on an L1L2 point-to-point circuit will result in an error of InconsistentValue.

```

    This object follows the ResettingTimer behavior."
    REFERENCE "{ISIS.aoi isISHelloTimer (45)}"
    DEFVAL { 3000 }
 ::= { isisCircLevelEntry 9 }

isisCircLevelDRHelloTimer OBJECT-TYPE
    SYNTAX Unsigned32 (10..120000)
    UNITS "milliseconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Period, in milliseconds, between Hello PDUs on
         multiaccess networks when this IS is the Designated
         Intermediate System. This object follows the
         ResettingTimer behavior."
    REFERENCE "{ISIS.aoi isISHelloTimer (45)}"
    DEFVAL { 1000 }
 ::= { isisCircLevelEntry 10 }

isisCircLevelLSPThrottle OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (1..65535)
    UNITS "milliseconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Minimal interval of time, in milliseconds, between
         transmissions of LSPs on an interface at this level."
    REFERENCE
        "{ISIS.aoi minimumBroadcastLSPTransmissionInterval (5)}"
    DEFVAL { 30 }
 ::= { isisCircLevelEntry 11 }

isisCircLevelMinLSPRetransInt OBJECT-TYPE
    SYNTAX Unsigned32 (1..300)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Minimum interval, in seconds, between re-transmission of
         an LSP at this level. This object follows the
         ResettingTimer behavior.

        Note that isisCircLevelLSPThrottle controls
        how fast we send back-to-back LSPs. This variable
        controls how fast we re-send the same LSP."
    REFERENCE "{ISIS.aoi minimumLSPTransmissionInterval (5)}"
    DEFVAL { 5 }
 ::= { isisCircLevelEntry 12 }

```

```

isisCircLevelCSNPInterval OBJECT-TYPE
    SYNTAX Unsigned32 (1..600)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Interval of time, in seconds, between periodic
         transmission of a complete set of CSNPs on
         multiaccess networks if this router is the
         designated router at this level.
         This object follows the ResettingTimer behavior."
    REFERENCE "{ISIS.aoi completeSNPInterval (8)}"
    DEFVAL { 10 }
 ::= { isisCircLevelEntry 13 }

isisCircLevelPartSNPInterval OBJECT-TYPE
    SYNTAX Unsigned32 (1..120)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Minimum interval, in seconds, between sending Partial
         Sequence Number PDUs at this level. This object
         follows the ResettingTimer behavior."
    REFERENCE "{ISIS.aoi partialSNPInterval (14)}"
    DEFVAL { 2 }
 ::= { isisCircLevelEntry 14 }

-- isisSystemCounterTable keeps track of system-wide events.

isisSystemCounterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisSystemCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "System-wide counters for this Intermediate System."
 ::= { isisCounters 1 }

isisSystemCounterEntry OBJECT-TYPE
    SYNTAX IsisSystemCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "System-wide IS-IS counters."
    INDEX { isisSysStatLevel }
 ::= { isisSystemCounterTable 1 }

IsisSystemCounterEntry ::=

```

```

SEQUENCE {
    isisSysStatLevel
        IsisISLevel,
    isisSysStatCorrLSPs
        Counter32,
    isisSysStatAuthTypeFails
        Counter32,
    isisSysStatAuthFails
        Counter32,
    isisSysStatLSPDbaseOloads
        Counter32,
    isisSysStatManAddrDropFromAreas
        Counter32,
    isisSysStatAttemptToExMaxSeqNums
        Counter32,
    isisSysStatSeqNumSkips
        Counter32,
    isisSysStatOwnLSPPurges
        Counter32,
    isisSysStatIDFieldLenMismatches
        Counter32,
    isisSysStatPartChanges
        Counter32,
    isisSysStatSPFRuns
        Counter32,
    isisSysStatLSPErrors
        Counter32
}

isisSysStatLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level that this entry describes."
::= { isisSystemCounterEntry 1 }

isisSysStatCorrLSPs OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of corrupted in-memory frames"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of corrupted in-memory LSPs detected.

        LSPs received from the wire with a bad checksum
        are silently dropped and are not counted.

```

```
LSPs received from the wire with parse errors  
are counted by isisSysStatLSPErrors."  
REFERENCE "{ISIS.aoi corruptedLSPsDetected (19)}"  
 ::= { isisSystemCounterEntry 2 }  
  
isisSysStatAuthTypeFails OBJECT-TYPE  
 SYNTAX Counter32  
 UNITS "Number of frames with authentication type mismatches"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
   "The number of authentication type mismatches recognized  
    by this Intermediate System."  
 ::= { isisSystemCounterEntry 3 }  
  
isisSysStatAuthFails OBJECT-TYPE  
 SYNTAX Counter32  
 UNITS "Number of frames with authentication key failures"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
   "The number of authentication key failures recognized  
    by this Intermediate System."  
 ::= { isisSystemCounterEntry 4 }  
  
isisSysStatLSPDbaseOloads OBJECT-TYPE  
 SYNTAX Counter32  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
   "Number of times the LSP database has become  
    overloaded."  
REFERENCE "{ISIS.aoi lsPL1DatabaseOverloads (20)}"  
 ::= { isisSystemCounterEntry 5 }  
  
isisSysStatManAddrDropFromAreas OBJECT-TYPE  
 SYNTAX Counter32  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
   "Number of times a manual address has been dropped from  
    the area."  
REFERENCE "{ISIS.aoi manualAddressesDroppedFromArea (21)}"  
 ::= { isisSystemCounterEntry 6 }  
  
isisSysStatAttemptToExMaxSeqNums OBJECT-TYPE  
 SYNTAX Counter32  
 MAX-ACCESS read-only
```

```
STATUS current
DESCRIPTION
    "Number of times the IS has attempted to exceed the
     maximum sequence number."
REFERENCE
    "{ISIS.aoi attemptsToExceedmaximumSequenceNumber (22)}"
::= { isisSystemCounterEntry 7 }

isisSysStatSeqNumSkips OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a sequence number skip has occurred."
    REFERENCE "{ISIS.aoi sequenceNumberSkips (23)}"
::= { isisSystemCounterEntry 8 }

isisSysStatOwnLSPPurges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a zero-aged copy of the system's own LSP
         is received from some other node."
    REFERENCE "{ISIS.aoi ownLSPPurges (24)}"
::= { isisSystemCounterEntry 9 }

isisSysStatIDFieldLenMismatches OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with ID length mismatches"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a PDU is received with a different value
         for ID field length from that of the receiving system."
    REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
::= { isisSystemCounterEntry 10 }

isisSysStatPartChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Partition changes."
::= { isisSystemCounterEntry 11 }

isisSysStatSPFRuns OBJECT-TYPE
    SYNTAX Counter32
```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of times we ran SPF at this level."
::= { isisSystemCounterEntry 12 }

isisSysStatLSPErrors OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with errors that we have received"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of LSPs with errors we have received."
::= { isisSystemCounterEntry 13 }

-- isisCircuitCounterTable keeps track of events
-- specific to a circuit and a level

isisCircuitCounterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisCircuitCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Circuit specific counters for this
         Intermediate System."
::= { isisCounters 2 }

isisCircuitCounterEntry OBJECT-TYPE
    SYNTAX IsisCircuitCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An IsisCircuitCounterEntry exists for each circuit
         used by Integrated IS-IS on this system."
    INDEX { isisCircIndex,
            isisCircuitType }
::= { isisCircuitCounterTable 1 }

IsisCircuitCounterEntry ::= SEQUENCE {
    isisCircuitType
        INTEGER,
    isisCircAdjChanges
        Counter32,
    isisCircNumAdj
        Unsigned32,
    isisCircInitFails
        Counter32,
    isisCircRejAdjs
```

```

        Counter32,
isisCircIDFieldLenMismatches
        Counter32,
isisCircMaxAreaAddrMismatches
        Counter32,
isisCircAuthTypeFails
        Counter32,
isisCircAuthFails
        Counter32,
isisCircLANDesISChanges
        Counter32
}

isisCircuitType OBJECT-TYPE
    SYNTAX INTEGER
    {
        lanlevel1(1),
        lanlevel2(2),
        p2pcircuit(3)
    }
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "What type of circuit saw these counts?

The point-to-point Hello PDU includes
both L1 and L2, and ISs form a single
adjacency on point-to-point links.
Thus, we combine counts on
point-to-point links into one group."
::= { isisCircuitCounterEntry 1 }

isisCircAdjChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an adjacency state change has
        occurred on this circuit."
    REFERENCE "{ISIS.aoi changesInAdjacencyState (40)}"
::= { isisCircuitCounterEntry 2 }

isisCircNumAdj OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of adjacencies on this circuit."

```

```

REFERENCE "{ISIS.aoi changesInAdjacencyState (40)}"
::= { isisCircuitCounterEntry 3 }

isisCircInitFails OBJECT-TYPE
  SYNTAX Counter32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of times initialization of this circuit has
     failed. This counts events such as PPP NCP failures.
     Failures to form an adjacency are counted by
     isisCircRejAdjs."
::= { isisCircuitCounterEntry 4 }

isisCircRejAdjs OBJECT-TYPE
  SYNTAX Counter32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of times an adjacency has been rejected on
     this circuit."
  REFERENCE "{ISIS.aoi rejectedAdjacencies (42)}"
::= { isisCircuitCounterEntry 5 }

isisCircIDFieldLenMismatches OBJECT-TYPE
  SYNTAX Counter32
  UNITS "Number of frames with ID field length mismatch"
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of times an IS-IS control PDU with an ID
     field length different from that for this system has been
     received."
  REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
::= { isisCircuitCounterEntry 6 }

isisCircMaxAreaAddrMismatches OBJECT-TYPE
  SYNTAX Counter32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of times an IS-IS control PDU with a
     max area address field different from that for this
     system has been received."
  REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
::= { isisCircuitCounterEntry 7 }

isisCircAuthTypeFails OBJECT-TYPE

```

```
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of times an IS-IS control PDU with
     an auth type field different from that for this
     system has been received."
 ::= { isisCircuitCounterEntry 8 }

isisCircAuthFails OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an IS-IS control PDU with
         the correct auth type has failed to pass authentication
         validation."
 ::= { isisCircuitCounterEntry 9 }

isisCircLANDesISChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times the Designated IS has changed
         on this circuit at this level. If the circuit is
         point to point, this count is zero."
 ::= { isisCircuitCounterEntry 10 }

-- isisPacketCounterTable keeps track of the number of IS-IS
-- control packets sent and received at each level

isisPacketCounterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisPacketCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Information about IS-IS protocol traffic at one level,
         on one circuit, in one direction."
 ::= { isisCounters 3 }

isisPacketCounterEntry OBJECT-TYPE
    SYNTAX IsisPacketCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Information about IS-IS protocol traffic at one level,
         on one circuit, in one direction."
```

```
INDEX { isisCircIndex,
         isisPacketCountLevel,
         isisPacketCountDirection }
 ::= { isisPacketCounterTable 1 }

IsisPacketCounterEntry ::==
SEQUENCE {
    isisPacketCountLevel
        IsisISLevel,
    isisPacketCountDirection
        INTEGER,
    isisPacketCountIHello
        Counter32,
    isisPacketCountISHello
        Counter32,
    isisPacketCountESHello
        Counter32,
    isisPacketCountLSP
        Counter32,
    isisPacketCountCSNP
        Counter32,
    isisPacketCountPSNP
        Counter32,
    isisPacketCountUnknown
        Counter32
}
isisPacketCountLevel OBJECT-TYPE
SYNTAX IsisISLevel
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "The level at which these PDU counts have been collected."
 ::= { isisPacketCounterEntry 1 }

isisPacketCountDirection OBJECT-TYPE
SYNTAX INTEGER
{
    sending(1),
    receiving(2)
}
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "Were we sending or receiving these PDUs?"
 ::= { isisPacketCounterEntry 2 }

isisPacketCountIHello OBJECT-TYPE
```

```
SYNTAX Counter32
UNITS "Number of IS-IS Hellos frames seen in this direction
      at this level"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "The number of IS-IS Hello PDUs seen in this
   direction at this level.

  Point-to-Point IIH PDUs are counted at
  the lowest enabled level: at L1 on L1 or L1L2 circuits,
  and at L2 otherwise."
REFERENCE "{ISIS.aoi isISControlPDUsSent (43)}"
::= { isisPacketCounterEntry 3 }

isisPacketCountISHello OBJECT-TYPE
  SYNTAX Counter32
  UNITS "Number of ES-IS frames seen in this direction at
        this level."
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of ES-IS Hello PDUs seen in this
     direction.  ISH PDUs are counted at the
     lowest enabled level: at L1 on L1 or L1L2
     circuits, and at L2 otherwise."
::= { isisPacketCounterEntry 4 }

isisPacketCountESHello OBJECT-TYPE
  SYNTAX Counter32
  UNITS "Number of ES Hello frames seen in this direction at
        this level"
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The number of ES Hello PDUs seen in this
     direction.  ESH PDUs are counted at the
     lowest enabled level: at L1 on L1 or L1L2
     circuits, and at L2 otherwise."
::= { isisPacketCounterEntry 5 }

isisPacketCountLSP OBJECT-TYPE
  SYNTAX Counter32
  UNITS "Number of IS-IS LSP frames seen in this direction at
        this level"
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
```

```
"The number of IS-IS LSPs seen in this
direction at this level."
REFERENCE "{ISIS.aoi isISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 6 }

isisPacketCountCSNP OBJECT-TYPE
SYNTAX Counter32
UNITS "Number of IS-IS CSNP frames seen in this direction at
this level"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of IS-IS CSNPs seen in this
direction at this level."
REFERENCE "{ISIS.aoi isISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 7 }

isisPacketCountPSNP OBJECT-TYPE
SYNTAX Counter32
UNITS "Number of IS-IS PSNP frames seen in this direction at
this level"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of IS-IS PSNPs seen in this
direction at this level."
REFERENCE "{ISIS.aoi isISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 8 }

isisPacketCountUnknown OBJECT-TYPE
SYNTAX Counter32
UNITS "Number of unknown IS-IS frames seen at this level"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of unknown IS-IS PDUs seen
at this level."
REFERENCE "{ISIS.aoi isISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 9 }

-- The IS Adjacency Table
--
-- Each adjacency to an IS corresponds to one entry in this
-- table.

isisISAdjTable OBJECT-TYPE
SEQUENCE OF IsisISAdjEntry
MAX-ACCESS not-accessible
```

```
STATUS current
DESCRIPTION
    "The table of adjacencies to Intermediate Systems."
::= { isisISAdj 1 }

isisISAdjEntry OBJECT-TYPE
    SYNTAX IsisISAdjEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry corresponds to one adjacency to an
         Intermediate System on this system.

        Dynamically learned rows do not survive an agent reboot."
    INDEX { isisCircIndex,
            isisISAdjIndex }
::= { isisISAdjTable 1 }

IsisISAdjEntry ::=

SEQUENCE {
    isisISAdjIndex
        Unsigned32,
    isisISAdjState
        INTEGER,
    isisISAdj3WayState
        INTEGER,
    isisISAdjNeighSNPAAddress
        IsisOSINSAddress,
    isisISAdjNeighSysType
        INTEGER,
    isisISAdjNeighSysID
        IsisSystemID,
    isisISAdjNbrExtendedCircID
        Unsigned32,
    isisISAdjUsage
        IsisLevel,
    isisISAdjHoldTimer
        IsisUnsigned16TC,
    isisISAdjNeighPriority
        IsisISPRIORITY,
    isisISAdjLastUpTime
       TimeStamp
}

isisISAdjIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
```

```

DESCRIPTION
"A unique value identifying the IS adjacency from all
other such adjacencies on this circuit. This value is
automatically assigned by the system when the adjacency
is created."
 ::= { isisisAdjEntry 1 }

isisISAdjState OBJECT-TYPE
SYNTAX INTEGER
{
    down (1),
    initializing (2),
    up (3),
    failed(4)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The state of the adjacency."
REFERENCE "{ISIS.aoi adjacencyState (78)}"
 ::= { isisisAdjEntry 2 }

isisISAdj3WayState OBJECT-TYPE
SYNTAX INTEGER
{
    up (0),
    initializing (1),
    down (2),
    failed (3)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The 3Way state of the adjacency. These are picked
to match the historical on-the-wire representation
of the 3Way state and are not intended to match
isisISAdjState."
REFERENCE "{ RFC 3373 }"
 ::= { isisisAdjEntry 3 }

isisISAdjNeighSNPAAddress OBJECT-TYPE
SYNTAX IsisOSINSAAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The SNPA address of the neighboring system."
REFERENCE "{ISIS.aoi neighbourSNPAAddress (79)}"
 ::= { isisisAdjEntry 4 }

```

```

isisISAdjNeighSysType OBJECT-TYPE
  SYNTAX INTEGER
  {
    11IntermediateSystem(1),
    12IntermediateSystem(2),
    11L2IntermediateSystem(3),
    unknown(4)
  }
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The type of the neighboring system."
  REFERENCE "{ISIS.aoi neighbourSystemType (80)}"
 ::= { isisISAdjEntry 5 }

isisISAdjNeighSysID OBJECT-TYPE
  SYNTAX IsisSystemID
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The system ID of the neighboring Intermediate
     System."
  REFERENCE "{ISIS.aoi neighbourSystemIds (83)}"
 ::= { isisISAdjEntry 6 }

isisISAdjNbrExtendedCircID OBJECT-TYPE
  SYNTAX Unsigned32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The 4-byte Extended Circuit ID learned from the
     Neighbor during 3-way handshake, or 0."
 ::= { isisISAdjEntry 7 }

isisISAdjUsage OBJECT-TYPE
  SYNTAX IsisLevel
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "How is the adjacency used? On a point-to-point link,
     this might be level1and2, but on a LAN, the usage will
     be level1 on the adjacency between peers at L1,
     and level2 for the adjacency between peers at L2."
  REFERENCE "{ISIS.aoi adjacencyUsage (82)}"
 ::= { isisISAdjEntry 8 }

isisISAdjHoldTimer OBJECT-TYPE
  SYNTAX IsisUnsigned16TC (1..65535)

```

```

UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The holding time, in seconds, for this adjacency.
     This value is based on received IIH PDUs and
     the elapsed time since receipt."
REFERENCE "{ISIS.aoi holdingTimer (85)}"
::= { isisISAdjEntry 9 }

isisISAdjNeighPriority OBJECT-TYPE
    SYNTAX IsisISPRIORITY
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Priority of the neighboring Intermediate System for
         becoming the Designated Intermediate System."
REFERENCE "{ISIS.aoi LANPriority (86)}"
::= { isisISAdjEntry 10 }

isisISAdjLastUpTime OBJECT-TYPE
    SYNTAX TimeStamp
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "When the adjacency most recently entered the state 'up',
         measured in hundredths of a second since the last
         re-initialization of the network management subsystem.
         Holds 0 if the adjacency has never been in state 'up'.""
::= { isisISAdjEntry 11 }

-- The IS Adjacency Area Address Table

-- The IS Adjacency Area Address Table contains the set of
-- Area Addresses of neighboring
-- Intermediate Systems as reported in IIH PDUs.

isisISAdjAreaAddrTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjAreaAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "This table contains the set of Area Addresses of
         neighboring Intermediate Systems as reported in received
         IIH PDUs."
REFERENCE "{ISIS.aoi areaAddressesOfNeighbour (84)}"
::= { isisISAdj 2 }

```

```

isisISAdjAreaAddrEntry OBJECT-TYPE
  SYNTAX IsisISAdjAreaAddrEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry contains one Area Address reported by a
     neighboring Intermediate System in its IIH PDUs.

    Dynamically learned rows do not survive an agent reboot."
  INDEX { isisCircIndex,
          isisISAdjIndex,
          isisISAdjAreaAddrIndex }
 ::= { isisISAdjAreaAddrTable 1 }

IsisISAdjAreaAddrEntry ::=
  SEQUENCE {
    isisISAdjAreaAddrIndex
      Unsigned32,
    isisISAdjAreaAddress
      IsisOSINSAddress
  }

isisISAdjAreaAddrIndex OBJECT-TYPE
  SYNTAX Unsigned32(1..4294967295)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An index for the areas associated with one neighbor.
     This provides a simple way to walk the table."
 ::= { isisISAdjAreaAddrEntry 1 }

isisISAdjAreaAddress OBJECT-TYPE
  SYNTAX IsisOSINSAddress
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "One Area Address as reported in IIH PDUs received from
     the neighbor."
 ::= { isisISAdjAreaAddrEntry 2 }

-- The IS Adjacency IP Address Table

-- The IS Adjacency IP Address Table contains the
-- set of IP Addresses of neighboring Intermediate Systems
-- as reported in received IIH PDUs.

isisISAdjIPAddrTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisISAdjIPAddrEntry

```

```

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
  "This table contains the set of IP Addresses of
  neighboring Intermediate Systems as reported in received
  IIH PDUs."
 ::= { isisISAdj 3 }

isisISAdjIPAddrEntry OBJECT-TYPE
  SYNTAX IsisISAdjIPAddrEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry contains one IP Address reported by a
    neighboring Intermediate System in its IIH PDUs.

    Dynamically learned rows do not survive an agent reboot."
INDEX { isisCircIndex,
        isisISAdjIndex,
        isisISAdjIPAddrIndex
      }
 ::= { isisISAdjIPAddrTable 1 }

IsisISAdjIPAddrEntry ::=
SEQUENCE {
  isisISAdjIPAddrIndex
  Unsigned32,
  isisISAdjIPAddrType
  InetAddressType,
  isisISAdjIPAddrAddress
  InetAddress
}

isisISAdjIPAddrIndex OBJECT-TYPE
  SYNTAX Unsigned32(1..4294967295)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An index to this table that identifies the IP addresses
    to which this entry belongs."
 ::= { isisISAdjIPAddrEntry 1 }

isisISAdjIPAddrType OBJECT-TYPE
  SYNTAX InetAddressType
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The type of one IP Address as reported in IIH PDUs

```

```

        received from the neighbor."
 ::= { isisISAdjIPAddrEntry 2 }

isisISAdjIPAddrAddress OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "One IP Address as reported in IIH PDUs received from the
         neighbor.

        The type of this address is determined by the value of
         the isisISAdjIPAddrType object."
 ::= { isisISAdjIPAddrEntry 3 }

-- The IS Adjacency Protocol Supported Table
--
-- The IS Adjacency Protocol Supported Table contains the set of
-- protocols supported by neighboring
-- Intermediate Systems as reported in received IIH PDUs.

isisISAdjProtSuppTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjProtSuppEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "This table contains the set of protocols supported by
         neighboring Intermediate Systems as reported in received
         IIH PDUs."
 ::= { isisISAdj 4 }

isisISAdjProtSuppEntry OBJECT-TYPE
    SYNTAX IsisISAdjProtSuppEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry contains one protocol supported by a
         neighboring Intermediate System as reported in its IIH
         PDUs.

        Dynamically learned rows do not survive an agent reboot."
INDEX { isisCircIndex,
        isisISAdjIndex,
        isisISAdjProtSuppProtocol }
 ::= { isisISAdjProtSuppTable 1 }

IsisISAdjProtSuppEntry ::=

SEQUENCE {

```

```

isisISAdjProtSuppProtocol
  IsisSupportedProtocol
}

isisISAdjProtSuppProtocol OBJECT-TYPE
  SYNTAX IsisSupportedProtocol
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "One supported protocol as reported in IIH PDUs received
     from the neighbor."
 ::= { isisISAdjProtSuppEntry 1 }

-- The Reachable Address Group
--
-- The Reachable Address Table
-- Each entry records information about a reachable address
-- (NSAP or address prefix) manually configured on the system
-- or learned through another protocol.

isisRATable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisRAEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The table of Reachable Addresses to NSAPs or Address
     Prefixes."
 ::= { isisReachAddr 1 }

isisRAEntry OBJECT-TYPE
  SYNTAX IsisRAEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry defines a configured Reachable Address
     to an NSAP or Address Prefix.

     Dynamically created rows MUST survive an agent reboot."
INDEX { isisCircIndex,
        isisRAIndex }
 ::= { isisRATable 1 }

IsisRAEntry ::=
  SEQUENCE {
    isisRAIndex
      Unsigned32,
    isisRAExistState
      RowStatus,

```

```
isisRAAdminState
    IsisAdminState,
isisRAAddrPrefix
    IsisOSINSAddress,
isisRAMapType
    INTEGER,
isisRAMetric
    IsisDefaultMetric,
isisRASMetricType
    IsisMetricType,
isisRASNPAAddress
    IsisOSINSAddress,
isisRASNPAMask
    IsisOSINSAddress,
isisRASNPAPrefix
    IsisOSINSAddress,
isisRAType
    INTEGER
}

isisRAIndex OBJECT-TYPE
SYNTAX Unsigned32(1..4294967295)
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The identifier for this isisRAEntry. This value must be
unique amongst all Reachable Addresses on the same parent
Circuit."
::= { isisRAEntry 1 }

isisRAExistState OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The existence state of this Reachable Address. This
object follows the ManualOrAutomatic behaviors. Support
for 'createAndWait' and 'notInService' is not required.

A row entry cannot be modified when the value of this
object is 'active'.""
::= { isisRAEntry 2 }

isisRAAdminState OBJECT-TYPE
SYNTAX IsisAdminState
MAX-ACCESS read-create
STATUS current
DESCRIPTION
```

```

    "The administrative state of the Reachable Address. This
    object follows the ManualOrAutomatic behaviors."
DEFVAL { off }
 ::= { isisRAEntry 3 }

isisRAAddrPrefix OBJECT-TYPE
SYNTAX IsisOSINSAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The destination of this Reachable Address. This is an
    Address Prefix. This object follows the
    ReplaceOnlyWhileDisabled and ManualOrAutomatic
    behaviors."
REFERENCE "{ISIS.aoi addressPrefix (98)}"
 ::= { isisRAEntry 4 }

isisRAMapType OBJECT-TYPE
SYNTAX INTEGER
{
    none (1),
    explicit (2),
    extractIDI (3),
    extractDSP (4)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The type of mapping to be employed to ascertain the SNPA
    Address that should be used in forwarding PDUs for this
    Reachable Address prefix. This object follows the
    ManualOrAutomatic behavior. The following values of
    mapping type are defined:

        none: The mapping is null because the neighbor SNPA is
            implicit by nature of the subnetwork (e.g., a
            point-to-point linkage).

        explicit: The subnetwork addresses in the object
            isisRASNPAAddress are to be used.

        extractIDI: The SNPA is embedded in the IDI of
            the destination NSAP Address. The mapping
            algorithm extracts the SNPA to be used
            according to the format and encoding rules of
            ISO8473/Add2. This SNPA extraction algorithm can
            be used in conjunction with Reachable Address
            prefixes from the X.121, F.69, E.163, and E.164

```

addressing subdomains.

extractDSP: All, or a suffix, of the SNPA is embedded in the DSP of the destination address. This SNPA extraction algorithm extracts the embedded subnetwork addressing information by performing a logical AND of the isisRASNPAmask object value with the destination address. The part of the SNPA extracted from the destination NSAP is appended to the isisRASNPAprefix object value to form the next hop subnetwork addressing information."

REFERENCE "{ISO10589-ISIS.aoi mappingType (107)}"
 ::= { isisRAEntry 5 }

isisRAMetric OBJECT-TYPE
 SYNTAX IsisDefaultMetric
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "The metric value for reaching the specified prefix over this circuit. This object follows the ManualOrAutomatic behavior."
 REFERENCE "{ISIS.aoi DefaultMetric (99)}"
 DEFVAL { 20 }
 ::= { isisRAEntry 6 }

isisRAMetricType OBJECT-TYPE
 SYNTAX IsisMetricType
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "Indicates whether the metric is internal or external. This object follows the ManualOrAutomatic behavior."
 REFERENCE "{ISIS.aoi DefaultMetricType (103)}"
 DEFVAL { internal }
 ::= { isisRAEntry 7 }

isisRASNPAAddress OBJECT-TYPE
 SYNTAX IsisOSINSAddress
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "The SNPA Address to which a PDU may be forwarded in order to reach a destination that matches the address prefix of the Reachable Address. This object follows the

```

    ManualOrAutomatic behavior."
    REFERENCE "{ISIS.aoi SNPAAAddresses (109)}"
-- Note only one address may be specified per Reachable Address
-- in the MIB
    DEFVAL { ''H }
    ::= { isisRAEntry 8 }

isisRASNPAMask OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "A bit mask with 1 bit indicating the positions in the
         effective destination address from which embedded SNPA
         information is to be extracted. For the extraction, the
         first octet of the isisRASNPAMask object value is aligned
         with the first octet (AFI) of the NSAP Address. If the
         isisRASNPAMask object value and NSAP Address are of
         different lengths, the shorter of the two is logically
         padded with zeros before performing the extraction. This
         object follows the ManualOrAutomatic behavior."
    REFERENCE "{ISIS.aoi SNPAMask (122)}"
    DEFVAL { '00'H }
    ::= { isisRAEntry 9 }

isisRASNPAPrefix OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "A fixed SNPA prefix for use when the isisRAMapType is
         extractDSP. The SNPA Address to use is formed by
         concatenating the fixed SNPA prefix with a variable SNPA
         part that is extracted from the effective destination
         address. For Reachable Address prefixes in which the
         entire SNPA is embedded in the DSP, the SNPA Prefix shall
         be null. This object follows the ManualOrAutomatic
         behavior."
    REFERENCE "{ISIS.aoi SNPAPrefix (123)}"
    DEFVAL { '00'H }
    ::= { isisRAEntry 10 }

isisRAType OBJECT-TYPE
    SYNTAX INTEGER
    {
        manual (1),
        automatic (2)
    }

```

```

MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "The type of Reachable address. Those of type
  manual are created by the network manager. Those
  of type automatic are created through propagation
  of routing information from another routing
  protocol (e.g., IDR). "
DEFVAL {manual}
 ::= {isisRAEntry 11 }

```

-- The IP Reachable Address Table

-- Each entry records information about one IP reachable
-- address manually configured on this system or learned from
-- another protocol.

```

isisIPRATable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisIPRAEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The table of IP Reachable Addresses to networks,
    subnetworks, or hosts either manually configured or
    learned from another protocol."
 ::= { isisIPReachAddr 1 }

```

```

isisIPRAEntry OBJECT-TYPE
  SYNTAX IsisIPRAEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry defines an IP Reachable Address to a network,
    subnetwork, or host.

```

Each IP Reachable Address may have multiple entries in the table, one for each equal cost path to the reachable address.

Dynamically created rows MUST survive an agent reboot.

Implementers need to be aware that if the total number of elements (octets or sub-identifiers) in isisIPRADest, isisIPRADestPrefixLen, and isisIPRANextHopIndex is too great, then OIDs of column instances in this table will have more than 128 subidentifiers and cannot be accessed using SNMPv1,

```

SNMPv2c, or SNMPv3."
INDEX { isisSysLevelIndex,
         isisIPRADestType,
         isisIPRADest,
         isisIPRADestPrefixLen,
         isisIPRANextHopIndex }
 ::= { isisIPRATable 1 }

IsisIPRAEntry ::==
SEQUENCE {
    isisIPRADestType
        InetAddressType,
    isisIPRADest
        InetAddress,
    isisIPRADestPrefixLen
        InetAddressPrefixLength,
    isisIPRANextHopIndex
        Unsigned32,
    isisIPRANextHopType
        InetAddressType,
    isisIPRANextHop
        InetAddress,
    isisIPRAType
        INTEGER,
    isisIPRAExistState
        RowStatus,
    isisIPRAAdminState
        IsisAdminState,
    isisIPRAMetric
        IsisDefaultMetric,
    isisIPRAMetricType
        IsisMetricType,
    isisIPRAFullMetric
        IsisFullMetric,
    isisIPRASNPAAddress
        IsisOSINSAddress,
    isisIPRASourceType
        INTEGER
}
}

isisIPRADestType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "The type of this IP Reachable Address."
 ::= { isisIPRAEntry 1 }

```

```

isisIPRADest OBJECT-TYPE
  SYNTAX InetAddress
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The destination of this IP Reachable Address. This is
     a network address, subnetwork address, or host
     address.

  The type of this address is determined by the value of
  the isisIPRADestType object.

 ::= { isisIPRAEntry 2 }

isisIPRADestPrefixLen OBJECT-TYPE
  SYNTAX InetAddressPrefixLength
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "The length of the IP Netmask for Reachability Address.

  The values for the index objects isisIPRADest and
  isisIPRADestPrefixLen must be consistent. When the value
  of isisIPRADest (excluding the zone index, if one
  is present) is x, then the bitwise logical-AND
  of x with the value of the mask formed from the
  corresponding index object isisIPRADestPrefixLen MUST be
  equal to x. If not, then the index pair is not
  consistent, and an inconsistentName error must be
  returned on SET or CREATE requests.

 ::= { isisIPRAEntry 3 }

isisIPRANextHopIndex OBJECT-TYPE
  SYNTAX Unsigned32(1..4294967295)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Index of next hop. Used when there are multiple Equal
     Cost Multipath alternatives for the same destination."
 ::= { isisIPRAEntry 4 }

isisIPRANextHopType OBJECT-TYPE
  SYNTAX InetAddressType
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The type of the IP next hop address."
 ::= { isisIPRAEntry 5 }

```

```
isisIPRANextHop OBJECT-TYPE
  SYNTAX InetAddress
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The IP next hop to this destination.

    The type of this address is determined by the value of
    the isisIPRANextHopType object."
 ::= { isisIPRAEntry 6 }

isisIPRAType OBJECT-TYPE
  SYNTAX INTEGER
  {
    manual (1),
    automatic (2)
  }
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The type of this IP Reachable Address. Those of type
    manual are created by the network manager. Those of type
    automatic are created through propagation of routing
    information from another routing protocol. This object
    follows the ManualOrAutomatic behavior."
 ::= { isisIPRAEntry 7 }

isisIPRAExistState OBJECT-TYPE
  SYNTAX RowStatus
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The state of this IP Reachable Address. This object
    follows the ExistenceState and ManualOrAutomatic
    behaviors. Support for 'createAndWait' and
    'notInService' is not required.

    A row entry cannot be modified when the value of this
    object is 'active'."
 ::= { isisIPRAEntry 8 }

isisIPRAAdminState OBJECT-TYPE
  SYNTAX IsisAdminState
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The administrative state of the IP Reachable Address. This
    object follows the IsisAdminState and ManualOrAutomatic
```

```
        behaviors."
DEFVAL { off }
 ::= { isisIPRAEntry 9 }

isisIPRAMetric OBJECT-TYPE
SYNTAX IsisDefaultMetric
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The metric value for reaching the specified
     destination over this circuit. This object follows the
     ManualOrAutomatic behavior."
DEFVAL { 10 }
 ::= { isisIPRAEntry 10 }

isisIPRAMetricType OBJECT-TYPE
SYNTAX IsisMetricType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Indicates whether the metric is internal or
     external. This object follows the ManualOrAutomatic
     behavior."
DEFVAL { internal }
 ::= { isisIPRAEntry 11 }

isisIPRAFullMetric OBJECT-TYPE
SYNTAX IsisFullMetric
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The wide metric value for reaching the specified
     destination over this circuit. This object follows the
     ManualOrAutomatic behavior."
DEFVAL { 10 }
 ::= { isisIPRAEntry 12 }

isisIPRASNPAAddress OBJECT-TYPE
SYNTAX IsisOSINSAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The SNPA Address to which a PDU may be forwarded in
     order to reach a destination that matches this IP
     Reachable Address. This object follows the
     ManualOrAutomatic behavior."
DEFVAL { ''H }
 ::= { isisIPRAEntry 13 }
```

```

isisIPRAEntry OBJECT-TYPE
SYNTAX INTEGER
{
    static (1),
    direct (2),
    ospfv2 (3),
    ospfv3 (4),
    isis (5),
    rip (6),
    igrp (7),
    eigrp (8),
    bgp (9),
    other (10)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The origin of this route."
::= { isisIPRAEntry 14 }

-- The LSP Database Table
--
-- The first table provides Summary Information about LSPs
-- The next table provides a complete record

isisLSPSummaryTable OBJECT-TYPE
SYNTAX SEQUENCE OF IsisLSPSummaryEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "The table of LSP Headers."
::= { isisLSPDataBase 1 }

isisLSPSummaryEntry OBJECT-TYPE
SYNTAX IsisLSPSummaryEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "Each entry provides a summary describing an
     LSP currently stored in the system.

     Dynamically learned rows will not survive an
     agent reboot."
INDEX { isisLSPLevel,
        isisLSPID }
::= { isisLSPSummaryTable 1 }

IsisLSPSummaryEntry ::=


```

```

SEQUENCE {
    isisLSPLevel
        IsisISLevel,
    isisLSPID
        IsisLinkStatePDUID,
    isisLSPSeq
        Unsigned32,
    isisLSPZeroLife
        TruthValue,
    isisLSPChecksum
        IsisUnsigned16TC,
    isisLSPLifetimeRemain
        IsisUnsigned16TC,
    isisLSPDULength
        IsisUnsigned16TC,
    isisLSPAttributes
        IsisUnsigned8TC
}

isisLSPLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "At which level does this LSP appear?"
::= { isisLSPSummaryEntry 1 }

isisLSPID OBJECT-TYPE
    SYNTAX IsisLinkStatePDUID
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The 8-byte LSP ID for this Link State PDU."
::= { isisLSPSummaryEntry 2 }

isisLSPSeq OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The sequence number for this LSP."
::= { isisLSPSummaryEntry 3 }

isisLSPZeroLife OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION

```

```

        "Is this LSP being purged by this system?"
::= { isisLSPSummaryEntry 4 }

isisLSPChecksum OBJECT-TYPE
  SYNTAX IsisUnsigned16TC
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The 16-bit Fletcher Checksum for this LSP."
::= { isisLSPSummaryEntry 5 }

isisLSPLifetimeRemain OBJECT-TYPE
  SYNTAX IsisUnsigned16TC
  UNITS "seconds"
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The remaining lifetime, in seconds, for this LSP."
::= { isisLSPSummaryEntry 6 }

isisLSPPDULength OBJECT-TYPE
  SYNTAX IsisUnsigned16TC
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The length of this LSP."
::= { isisLSPSummaryEntry 7 }

isisLSPAttributes OBJECT-TYPE
  SYNTAX IsisUnsigned8TC
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "Flags carried by the LSP."
::= { isisLSPSummaryEntry 8 }

-- LSP Table
--
-- The full LSP as a sequence of {Type, Len, Value} tuples
-- Since the underlying LSP may have changed while downloading
-- TLVs, we provide the Sequence number and Checksum for each
-- LSP TLV, so the network manager may verify that they are
-- still working on the same version of the LSP.

isisLSPTLVTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IsisLSPTLVEntry
  MAX-ACCESS not-accessible
  STATUS current

```

```

DESCRIPTION
    "The table of LSPs in the database."
::= { isisLSPDataBase 2 }

isisLSPTLVEntry OBJECT-TYPE
    SYNTAX IsisLSPTLVEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry describes a TLV within
         an LSP currently stored in the system.

        Dynamically learned rows will not survive an
        agent reboot."
    INDEX { isisLSPLevel,
            isisLSPID,
            isisLSPTLVIndex }
::= { isisLSPTLVTable 1 }

IsisLSPTLVEntry ::=
SEQUENCE {
    isisLSPTLVIndex
        Unsigned32,
    isisLSPTLVSeq
        Unsigned32,
    isisLSPTLVChecksum
        IsisUnsigned16TC,
    isisLSPTLVType
        IsisUnsigned8TC,
    isisLSPTLVLen
        IsisUnsigned8TC,
    isisLSPTLVValue
        OCTET STRING
}

isisLSPTLVIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The index of this TLV in the LSP. The first TLV has
         index 1, and the Nth TLV has an index of N."
::= { isisLSPTLVEntry 1 }

isisLSPTLVSeq OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current

```

```

DESCRIPTION
    "The sequence number for this LSP."
::= { isisLSPTLVEntry 2 }

isisLSPTLVCsum OBJECT-TYPE
SYNTAX IsisUnsigned16TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The 16-bit Fletcher Checksum for this LSP."
::= { isisLSPTLVEntry 3 }

isisLSPTLVtpe OBJECT-TYPE
SYNTAX IsisUnsigned8TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The type of this TLV."
::= { isisLSPTLVEntry 4 }

isisLSPTLVlEN OBJECT-TYPE
SYNTAX IsisUnsigned8TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The length of this TLV."
::= { isisLSPTLVEntry 5 }

isisLSPTLVValue OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(0..255))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The value of this TLV."
::= { isisLSPTLVEntry 6 }

```

-- The IS-IS Notification Table

-- The IS-IS Notification Table records fields that are
-- required for notifications

```

isisNotificationEntry OBJECT IDENTIFIER
 ::= { isisNotification 1 }

isisNotificationSysLevelIndex OBJECT-TYPE
SYNTAX IsisLevel
MAX-ACCESS accessible-for-notify

```

```
STATUS current
DESCRIPTION
    "The system level for this notification."
::= { isisNotificationEntry 1 }

isisNotificationCircIfIndex OBJECT-TYPE
    SYNTAX Unsigned32 (1..2147483647)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The identifier of this circuit relevant to
         this notification."
::= { isisNotificationEntry 2 }

isisPduLspId OBJECT-TYPE
    SYNTAX IsisLinkStatePDUID
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An Octet String that uniquely identifies
         a Link State PDU."
::= { isisNotificationEntry 3 }

isisPduFragment OBJECT-TYPE
    SYNTAX IsisPDUHeader
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds up to 64 initial bytes of a PDU that
         triggered the notification."
::= { isisNotificationEntry 4 }

isisPduFieldLen OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the System ID length reported in PDU we received."
::= { isisNotificationEntry 5 }

isisPduMaxAreaAddress OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the Max Area Addresses reported in a PDU
         we received."
::= { isisNotificationEntry 6 }
```

```
isisPduProtocolVersion OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the Protocol version reported in PDU we received."
::= { isisNotificationEntry 7 }

isisPduLspSize OBJECT-TYPE
    SYNTAX Unsigned32 (0..2147483647)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of LSP we received that is too
         big to forward."
::= { isisNotificationEntry 8 }

isisPduOriginatingBufferSize OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (0..16000)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of isisSysLevelOrigLSPBuffSize advertised
         by the peer in the originatingLSPBufferSize TLV.
         If the peer does not advertise this TLV, this
         value is set to 0."
::= { isisNotificationEntry 9 }

isisPduBufferSize OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (0..16000)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of LSP received from peer."
::= { isisNotificationEntry 10 }

isisPduProtocolsSupported OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..255))
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The list of protocols supported by an
         adjacent system. This may be empty."
::= { isisNotificationEntry 11 }

isisAdjState OBJECT-TYPE
    SYNTAX INTEGER
    {
```

```

        down (1),
        initializing (2),
        up (3),
        failed(4)
    }
MAX-ACCESS accessible-for-notify
STATUS current
DESCRIPTION
    "The current state of an adjacency."
::= { isisNotificationEntry 12 }

isisErrorOffset OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An offset to a problem in a PDU. If the problem
         is a malformed TLV, this points to the beginning
         of the TLV. If the problem is in the header, this
         points to the byte that is suspicious."
::= { isisNotificationEntry 13 }

isisErrorTLVType OBJECT-TYPE
    SYNTAX Unsigned32 (0..255)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The type for a malformed TLV."
::= { isisNotificationEntry 14 }

isisNotificationAreaAddress OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An Area Address."
::= { isisNotificationEntry 15 }

-- Notification definitions
--
-- Note that notifications can be disabled by setting
--     isisSysNotificationEnable false

isisDatabaseOverload NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisSysLevelState
    }

```

```
STATUS current
DESCRIPTION
  "This notification is generated when the system
  enters or leaves the Overload state. The number
  of times this has been generated and cleared is kept
  track of by isisSysStatLSPDbaseOloads."
 ::= { isisNotifications 1 }

isisManualAddressDrops NOTIFICATION-TYPE
OBJECTS {
  isisNotificationAreaAddress
}
STATUS current
DESCRIPTION
  "This notification is generated when one of the
  manual areaAddresses assigned to this system is
  ignored when computing routes. The object
  isisNotificationAreaAddress describes the area that
  has been dropped.

The number of times this event has been generated
is counted by isisSysStatManAddrDropFromAreas.

The agent must throttle the generation of
consecutive isisManualAddressDrops notifications
so that there is at least a 5-second gap between
notifications of this type. When notifications
are throttled, they are dropped, not queued for
sending at a future time."
 ::= { isisNotifications 2 }

isisCorruptedLSPDetected NOTIFICATION-TYPE
OBJECTS {
  isisNotificationSysLevelIndex,
  isisPduLspId
}
STATUS current
DESCRIPTION
  "This notification is generated when we find that
  an LSP that was stored in memory has become
  corrupted. The number of times this has been
  generated is counted by isisSysCorrLSPs.

We forward an LSP ID. We may have independent
knowledge of the ID, but in some implementations
there is a chance that the ID itself will be
corrupted."
```

```
::= { isisNotifications 3 }

isisAttemptToExceedMaxSequence NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisPduLspId
    }
    STATUS current
    DESCRIPTION
        "When the sequence number on an LSP we generate
         wraps the 32-bit sequence counter, we purge and
         wait to re-announce this information. This
         notification describes that event. Since these
         should not be generated rapidly, we generate
         an event each time this happens.

        While the first 6 bytes of the LSPID are ours,
        the other two contain useful information."

::= { isisNotifications 4 }

isisIDLenMismatch NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisPduFieldLen,
        isisNotificationCircIfIndex,
        isisPduFragment
    }
    STATUS current
    DESCRIPTION
        "A notification sent when we receive a PDU
         with a different value for the System ID Length.
         This notification includes an index to identify
         the circuit where we saw the PDU and the header of
         the PDU, which may help a network manager identify
         the source of the confusion.

        The agent must throttle the generation of
        consecutive isisIDLenMismatch notifications
        so that there is at least a 5-second gap between
        notifications of this type. When notifications
        are throttled, they are dropped, not queued for
        sending at a future time."

::= { isisNotifications 5 }

isisMaxAreaAddressesMismatch NOTIFICATION-TYPE
    OBJECTS {
```

```
isisNotificationSysLevelIndex,
isisPduMaxAreaAddress,
isisNotificationCircIfIndex,
isisPduFragment
}

STATUS current
DESCRIPTION
"A notification sent when we receive a PDU
with a different value for the Maximum Area
Addresses. This notification includes the
header of the packet, which may help a
network manager identify the source of the
confusion.

The agent must throttle the generation of
consecutive isisMaxAreaAddressesMismatch
notifications so that there is at least a 5-second
gap between notifications of this type. When
notifications are throttled, they are dropped, not
queued for sending at a future time."

 ::= { isisNotifications 6 }

isisOwnLSPPurge NOTIFICATION-TYPE
OBJECTS {
    isisNotificationSysLevelIndex,
    isisNotificationCircIfIndex,
    isisPduLspId
}
STATUS current
DESCRIPTION
"A notification sent when we receive a PDU
with our systemID and zero age. This
notification includes the circuit Index
and router ID from the LSP, if available,
which may help a network manager
identify the source of the confusion.

 ::= { isisNotifications 7 }

isisSequenceNumberSkip NOTIFICATION-TYPE
OBJECTS {
    isisNotificationSysLevelIndex,
    isisNotificationCircIfIndex,
    isisPduLspId
}
STATUS current
```

DESCRIPTION

"When we receive an LSP with our System ID and different contents, we may need to reissue the LSP with a higher sequence number.

We send this notification if we need to increase the sequence number by more than one. If two Intermediate Systems are configured with the same System ID, this notification will fire."

```
::= { isisNotifications 8 }
```

isisAuthenticationTypeFailure NOTIFICATION-TYPE

OBJECTS {

isisNotificationSysLevelIndex,
isisNotificationCircIfIndex,
isisPduFragment

}

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with the wrong authentication type field. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAuthenticationTypeFailure notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 9 }
```

isisAuthenticationFailure NOTIFICATION-TYPE

OBJECTS {

isisNotificationSysLevelIndex,
isisNotificationCircIfIndex,
isisPduFragment

}

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with an incorrect authentication information field. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAuthenticationFailure notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 10 }
```

isisVersionSkew NOTIFICATION-TYPE
OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduProtocolVersion,
 isisPduFragment
}
STATUS current
DESCRIPTION
 "A notification sent when we receive a Hello PDU from an IS running a different version of the protocol. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisVersionSkew notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 11 }
```

isisAreaMismatch NOTIFICATION-TYPE
OBJECTS {
 isisNotificationCircIfIndex,
 isisPduFragment
}
STATUS current
DESCRIPTION
 "A notification sent when we receive a Hello PDU from an IS that does not share any area address. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAreaMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 12 }
```

isisRejectedAdjacency NOTIFICATION-TYPE

```
OBJECTS {  
    isisNotificationSysLevelIndex,  
    isisNotificationCircIfIndex,  
    isisPduFragment  
}
```

STATUS current

DESCRIPTION

"A notification sent when we receive a Hello PDU from an IS but do not establish an adjacency for some reason.

The agent must throttle the generation of consecutive isisRejectedAdjacency notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 13 }
```

isisLSPTooLargeToPropagate NOTIFICATION-TYPE

```
OBJECTS {  
    isisNotificationSysLevelIndex,  
    isisNotificationCircIfIndex,  
    isisPduLspSize,  
    isisPduLspId  
}
```

STATUS current

DESCRIPTION

"A notification sent when we attempt to propagate an LSP that is larger than the dataLinkBlockSize for the circuit.

The agent must throttle the generation of consecutive isisLSPTooLargeToPropagate notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not

queued for sending at a future time."

::= { isisNotifications 14 }

isisOrigLSPBuffSizeMismatch NOTIFICATION-TYPE

OBJECTS {

isisNotificationSysLevelIndex,
isisNotificationCircIfIndex,
isisPduLspId,
isisPduOriginatingBufferSize,
isisPduBufferSize

}

STATUS current

DESCRIPTION

"A notification sent when a Level 1 LSP or Level 2 LSP is received that is larger than the local value for isisSysLevelOrigLSPBuffSize, or when an LSP is received that contains the supported Buffer Size option and the value in the PDU option field does not match the local value for isisSysLevelOrigLSPBuffSize. We pass up the size from the option field and the size of the LSP when one of them exceeds our configuration.

The agent must throttle the generation of consecutive isisOrigLSPBuffSizeMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 15 }

isisProtocolsSupportedMismatch NOTIFICATION-TYPE

OBJECTS {

isisNotificationSysLevelIndex,
isisNotificationCircIfIndex,
isisPduProtocolsSupported,
isisPduLspId,
isisPduFragment

}

STATUS current

DESCRIPTION

"A notification sent when a non-pseudonode segment 0 LSP is received that has no matching protocols supported. This may be because the system does not generate the field, or because there are no common elements. The list of protocols supported should be included in the notification: it may be

empty if the TLV is not supported, or if the TLV is empty.

The agent must throttle the generation of consecutive isisProtocolsSupportedMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 16 }
```

```
isisAdjacencyChange NOTIFICATION-TYPE
```

```
OBJECTS {
```

```
    isisNotificationSysLevelIndex,  
    isisNotificationCircIfIndex,  
    isisPduLspId,  
    isisAdjState
```

```
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
"A notification sent when an adjacency changes state, entering or leaving state up.
```

```
The first 6 bytes of the isisPduLspId are the SystemID of the adjacent IS.
```

```
The isisAdjState is the new state of the adjacency."
```

```
::= { isisNotifications 17 }
```

```
isisLSPErrorDetected NOTIFICATION-TYPE
```

```
OBJECTS {
```

```
    isisNotificationSysLevelIndex,  
    isisPduLspId,  
    isisNotificationCircIfIndex,  
    isisPduFragment,  
    isisErrorOffset,  
    isisErrorTLVType
```

```
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
"This notification is generated when we receive an LSP with a parse error. The isisCircIfIndex holds an index of the circuit on which the PDU arrived. The isisPduFragment holds the start of the LSP, and the isisErrorOffset points to the problem.
```

```
If the problem is a malformed TLV, isisErrorOffset points to the start of the TLV, and isisErrorTLVType
```

holds the value of the type.

If the problem is with the LSP header, isisErrorOffset points to the suspicious byte.

The number of such LSPs is accumulated in isisSysStatLSPErrors."

```
::= { isisNotifications 18 }

-- Agent Conformance Definitions
-- We define the objects a conformant agent must define

isisCompliances OBJECT IDENTIFIER ::= { isisConformance 1 }
isisGroups      OBJECT IDENTIFIER ::= { isisConformance 2 }

-- compliance statements

isisCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for agents that support
         the IS-IS MIB.

There are a number of INDEX objects that cannot be
represented in the form of OBJECT clauses in SMIv2,
but for which there are compliance requirements.
Those requirements and similar requirements for
related objects are expressed below, in
pseudo-OBJECT clause form, in this description:

-- OBJECT isisSummAddressType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4 Summary
--     Addresses and anticipates the support of
--     IPv6 addresses.
--

-- OBJECT isisRedistributeAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4
--     Redistribution Addresses and anticipates
--     the support of IPv6 addresses."
--
```

```

-- OBJECT isisISAdjIPAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--   The MIB requires support for IPv4
--   Adjacency Addresses and anticipates the
--   support of IPv6 addresses.
MODULE -- this module
MANDATORY-GROUPS {
    isisSystemGroup,
    isisCircuitGroup,
    isisISAdjGroup,
    isisNotificationObjectGroup,
    isisNotificationGroup
}
 ::= { isisCompliances 1 }
```

-- List of all groups, mandatory and optional
 isisAdvancedCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for agents that fully
 support the IS-IS MIB.

There are a number of INDEX objects that cannot be
 represented in the form of OBJECT clauses in SMIv2,
 but for which there are compliance requirements.
 Those requirements and similar requirements for
 related objects are expressed below, in
 pseudo-OBJECT clause form, in this description:

```

-- OBJECT isisSummAddressType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--   The MIB requires support for IPv4 Summary
--   Addresses and anticipates the support of
--   IPv6 addresses.
--
-- OBJECT isisRedistributeAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--   The MIB requires support for IPv4
--   Redistribution Addresses and anticipates
--   the support of IPv6 addresses."
```

```

-- 
-- 
-- OBJECT isisISAdjIPAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
-- 
-- DESCRIPTION
--   The MIB requires support for IPv4
--   Adjacency Addresses and anticipates the
--   support of IPv6 addresses.
-- 
-- 
-- OBJECT isisIPRADestType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
-- 
-- DESCRIPTION
--   The MIB requires support for IPv4 RA
--   Addresses and anticipates the support of
--   IPv6 addresses.
-- 
-- 
-- OBJECT isisIPRANextHopType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
-- 
-- DESCRIPTION
--   The MIB requires support for IPv4 NextHop
--   Addresses and anticipates the support of
--   IPv6 addresses.

MODULE -- this module
MANDATORY-GROUPS {
    isisSystemGroup,
    isisCircuitGroup,
    isisISAdjGroup,
    isisNotificationObjectGroup,
    isisNotificationGroup,
    isisISPDUCounterGroup,
    isisRATableGroup,
    isisisIPRADestGroup,
    isisLSPGroup
}
 ::= { isisCompliances 2 }

isisReadOnlyCompliance MODULE-COMPLIANCE
    STATUS      current
DESCRIPTION
    "When this MIB is implemented without support for
     read-create (i.e., in read-only mode), the
     implementation can claim read-only compliance. Such
     a device can then be monitored but cannot be

```

```
        configured with this MIB."
MODULE -- this module
    MANDATORY-GROUPS {
        isisSystemGroup,
        isisCircuitGroup,
        isisISAdjGroup
    }

OBJECT isisSysLevelType
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysID
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysMaxPathSplits
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysMaxLSPGenInt
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysPOLLHelloRate
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysWaitTime
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysAdminState
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysL2toL1Leaking
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisSysMaxAge
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisManAreaAddrExistState
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelOrigLSPBuffSize
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelMinLSPGenInt
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelSetOverload
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelSetOverloadUntil
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelMetricStyle
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelSPFConsiders
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysLevelTEEnabled
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysReceiveLSPBufferSize
MIN-ACCESS read-only
DESCRIPTION
```

```
"Write access is not required."
```

```
OBJECT isisSummAddrExistState  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisSummAddrMetric  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisSummAddrFullMetric  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisRedistributeAddrExistState  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircAdminState  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircExistState  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircType  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircExtDomain  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircLevelType  
MIN-ACCESS read-only  
DESCRIPTION  
    "Write access is not required."
```

```
OBJECT isisCircPassiveCircuit
```

```
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircMeshGroupEnabled
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircMeshGroup
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircSmallHellos
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircExtendedCircID
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircIfIndex
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCirc3WayEnabled
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelMetric
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelWideMetric
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelISPRIORITY
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelHelloMultiplier
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelHelloTimer
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelDRHelloTimer
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelLSPThrottle
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelMinLSPRetransInt
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelCSNPInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisCircLevelPartSNPInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required.

::= { isisCompliances 3 }
```

-- MIB Grouping

```
isisSystemGroup OBJECT-GROUP
    OBJECTS {
        isisSysVersion,
        isisSysLevelType,
        isisSysID,
        isisSysMaxPathSplits,
        isisSysMaxLSPGenInt,
        isisSysPollesHelloRate,
        isisSysWaitTime,
```

```
isisSysAdminState,
isisSysL2toL1Leaking,
isisSysMaxAge,
isisSysProtSupported,
isisSysNotificationEnable,
isisManAreaAddrExistState,
isisSysLevelOrigLSPBuffSize,
isisSysLevelMinLSPGenInt,
isisSysLevelState,
isisSysLevelSetOverload,
isisSysLevelSetOverloadUntil,
isisSysLevelMetricStyle,
isisSysLevelSPFConsiders,
isisSysLevelTEEnabled,
isisSysReceiveLSPBufferSize,
isisSummAddrExistState,
isisSummAddrMetric,
isisAreaAddr,
isisSummAddrFullMetric,
isisRedistributeAddrExistState,
isisRouterHostName,
isisRouterID,
isisSysStatCorrLSPs,
isisSysStatLSPDbaseOloads,
isisSysStatManAddrDropFromAreas,
isisSysStatAttemptToExMaxSeqNums,
isisSysStatSeqNumSkips,
isisSysStatOwnLSPPurges,
isisSysStatIDFieldLenMismatches,
isisSysStatPartChanges,
isisSysStatSPFRuns,
isisSysStatAuthTypeFails,
isisSysStatAuthFails,
isisSysStatLSPErrors
}
STATUS current
DESCRIPTION
    "The collections of objects used to manage an
     IS-IS router."
 ::= { isisGroups 1 }

isisCircuitGroup OBJECT-GROUP
    OBJECTS {
        isisNextCircIndex,
        isisCircAdminState,
        isisCircExistState,
        isisCircType,
        isisCircExtDomain,
```

```
isisCircLevelType,
isisCircAdjChanges,
isisCircNumAdj,
isisCircInitFails,
isisCircRejAdjs,
isisCircIDFieldLenMismatches,
isisCircMaxAreaAddrMismatches,
isisCircAuthTypeFails,
isisCircAuthFails,
isisCircLANDesISChanges,
isisCircPassiveCircuit,
isisCircMeshGroupEnabled,
isisCircMeshGroup,
isisCircSmallHellos,
isisCircLastUpTime,
isisCirc3WayEnabled,
isisCircExtendedCircID,
isisCircIfIndex,
isisCircLevelMetric,
isisCircLevelWideMetric,
isisCircLevelISPRIORITY,
isisCircLevelIDOctet,
isisCircLevelID,
isisCircLevelDesIS,
isisCircLevelHelloMultiplier,
isisCircLevelHelloTimer,
isisCircLevelDRHelloTimer,
isisCircLevelLSPThrottle,
isisCircLevelMinLSPRetransInt,
isisCircLevelCSNPInterval,
isisCircLevelPartSNPInterval
}
STATUS current
DESCRIPTION
    "The collections of objects used to describe an
     IS-IS Circuit."
 ::= { isisGroups 2 }

isisISAdjGroup OBJECT-GROUP
OBJECTS {
    isisisAdjState,
    isisisAdj3WayState,
    isisisAdjNeighSNPAAddress,
    isisisAdjNeighSysType,
    isisisAdjNeighSysID,
    isisisAdjNbrExtendedCircID,
    isisisAdjUsage,
    isisisAdjHoldTimer,
```

```
isisISAdjNeighPriority,
isisISAdjLastUpTime,
isisISAdjAreaAddress,
isisISAdjIPAddrType,
isisISAdjIPAddrAddress,
isisISAdjProtSuppProtocol
}
STATUS current
DESCRIPTION
    "The collections of objects used to manage an
     IS-IS Adjacency."
::= { isisGroups 3 }

isisNotificationObjectGroup OBJECT-GROUP
OBJECTS {
    isisNotificationSysLevelIndex,
    isisNotificationCircIfIndex,
    isisPduLspId,
    isisPduFragment,
    isisPduFieldLen,
    isisPduMaxAreaAddress,
    isisPduProtocolVersion,
    isisPduLspSize,
    isisPduOriginatingBufferSize,
    isisPduBufferSize,
    isisPduProtocolsSupported,
    isisAdjState,
    isisErrorOffset,
    isisErrorTLVType,
    isisNotificationAreaAddress
}
STATUS current
DESCRIPTION
    "The objects used to record notification parameters."
::= { isisGroups 4 }

isisNotificationGroup          NOTIFICATION-GROUP
NOTIFICATIONS {
    isisDatabaseOverload,
    isisManualAddressDrops,
    isisCorruptedLSPDetected,
    isisAttemptToExceedMaxSequence,
    isisIDLenMismatch,
    isisMaxAreaAddressesMismatch,
    isisOwnLSPPurge,
    isisSequenceNumberSkip,
    isisAuthenticationTypeFailure,
```

```
isisAuthenticationFailure,
isisVersionSkew,
isisAreaMismatch,
isisRejectedAdjacency,
isisLSPTooLargeToPropagate,
isisOrigLSPBuffSizeMismatch,
isisProtocolsSupportedMismatch,
isisAdjacencyChange,
isisLSPErrorDetected
}
STATUS current
DESCRIPTION
    "The collections of notifications sent by an IS."
::= { isisGroups 5 }

isisISPDUCounterGroup OBJECT-GROUP
OBJECTS {
    isisPacketCountIIHello,
    isisPacketCountISHello,
    isisPacketCountESHello,
    isisPacketCountLSP,
    isisPacketCountCSNP,
    isisPacketCountPSNP,
    isisPacketCountUnknown
}
STATUS current
DESCRIPTION
    "The collections of objects used to count protocol PDUs."
::= { isisGroups 6 }

isisRATableGroup OBJECT-GROUP
OBJECTS {
    isisRAExistState,
    isisRAAdminState,
    isisRAAddrPrefix,
    isisRAMapType,
    isisRAMetric,
    isisRAMetricType,
    isisRASNPAAddress,
    isisRASNPMask,
    isisRASNPAPrefix,
    isisRAType
}
STATUS current
DESCRIPTION
    "The collections of objects used to manage the
```

```
    reachable NSAP prefixes."
 ::= { isisGroups 7 }

isisISIPRADestGroup OBJECT-GROUP
OBJECTS {
    isisIPRANextHopType,
    isisIPRANextHop,
    isisIPRAType,
    isisIPRAExistState,
    isisIPRAAdminState,
    isisIPRAMetric,
    isisIPRAFullMetric,
    isisIPRAMetricType,
    isisIPRASNPAAddress,
    isisIPRASourceType
}
STATUS current
DESCRIPTION
    "The collections of objects used to manage configured
     IP addresses."
 ::= { isisGroups 8 }

isisLSPGroup OBJECT-GROUP
OBJECTS {
    isisLSPSeq,
    isisLSPZeroLife,
    isisLSPChecksum,
    isisLSPLifetimeRemain,
    isisLSPDULength,
    isisLSPAttributes,
    isisLSPTLVSeq,
    isisLSPTLVChecksum,
    isisLSPTLVType,
    isisLSPTLVLen,
    isisLSPTLVValue
}
STATUS current
DESCRIPTION
    "The collections of objects used to observe the LSP
     Database."
 ::= { isisGroups 9 }

END
```

5. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
isisMIB	{ mib-2 138 }

6. Acknowledgements

This MIB is based on a March 1994 document by Chris Gunner, who should be held blameless for the errors introduced since then. This version has been modified to include MIB-II syntax, to exclude portions of the protocol that are not relevant to IP, such as the ES-IS protocol, and to add management support for current practice.

We would like to thank the following individuals for constructive and valuable comments: Mike Bartlett, Neal Castagnoli, Ken Chapman, Joan Cucchiara, Satish Dattatri, Nagi Jonnala, Adrian Farrel, Shamik Ganguly, Les Ginsberg, Don Goodspeed, Jeff Gross, Jim Halpin, Jon Harrison, Dimitri Haskin, C. M. Heard, Peter Higginson, Christian Hopps, Laura Liu, Gavin McPherson, Kay Noguchi, Serge Maskalik, Z. Opalka, Jeff Pickering, Sundar Ramachandran, Swaminatha Ramalingam, Aravind Ravikumar, Juergen Schoenwaelder, Koen Vermeulen, Hans De Vleeschouwer, Bert Wijnen, and Bingzhang Zhao.

7. Security Considerations

Management information defined in this MIB may be considered sensitive in some network environments.

7.1. Discussion

This MIB may be used to manage an IP router, which is used to direct network traffic. The control of network traffic allows an attacker to deny service to a region of the network or to forward traffic to adversaries. By raising or lowering metrics, traffic may be directed to insecure portions of the network. By disabling the protocol on an interface, the network may be partitioned. Changes to the network topology will force all routers to recompute their routes. Periodic route changes have brought down networks in the past by subjecting routers to stressful recomputations.

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network

environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. Authentication of received SNMP requests and controlled access to management information should be employed in such environments.

We identify a set of threats and then list attributes that can be used in each form of attack. We discuss the effects that can be obtained by a single change to the variable in each class.

7.2. Threats

- Drop an Adjacency
- Drop all Peers
- Drop Subnetwork
- Split the Network
- Intermittent Outages
- Redirect Traffic
- Delay Convergence
- Avoid Detection
- Prevent Updates
- Hijack LAN
- Create Problems for CLNS Networks

7.2.1. Drop an Adjacency

By changing attributes that are used to peer, we can disrupt an adjacency and bring a link down.

```
isisCirc3WayEnabled  
isisCircAdminState  
isisCircExistState  
isisCircLevelDRHelloTimer  
isisCircLevelHelloTimer  
isisCircLevelType  
isisCircSmallHellos
```

7.2.2. Drop All Adjacencies

These attributes can be used to break some or all of a router's adjacencies. In the case of System ID, the adjacency may be restored. However, it will subject the network to additional stress.

```
isisSysLevelType  
isisManAreaAddrExistState  
isisSysAdminState  
isisSysID
```

7.2.3. Drop Subnetwork

This attribute can be used to stop advertisement of a subnetwork reachable through a single interface.

isisCircPassiveCircuit

7.2.4. Split the Network

If the network design depends upon Wide Metrics or TE, we can use these attributes to prevent traffic from passing through a router.

isisSysLevelMetricStyle
isisSysLevelOrigLSPBuffSize
isisSysLevelSPFConsiders
isisSysLevelTEEnabled
isisSysReceiveLSPBufferSize

7.2.5. Intermittent Outages

We can use these attributes to subject the network to a series of topology changes, or otherwise force extensive recomputations of routes.

isisSysLevelMinLSPGenInt
isisSysLevelSetOverload
isisSysLevelSetOverloadUntil
isisSysMaxAge
isisSysMaxLSPGenInt
isisSysL2toL1Leaking
isisSysID

7.2.6. Redirect Traffic

By changing attributes such as metrics, we can push traffic to different parts of the network. This may allow an intruder to observe data traffic from otherwise remote parts of the network.

We may also use these attributes to deny service to parts of the network.

isisSysMaxPathSplits
isisCircLevelMetric
isisCircLevelWideMetric
isisIPRAAdminState
isisIPRAExistState
isisIPRAFullMetric
isisIPRAMetric

```

isisIPRAMetricType
isisIPRANextHop
isisIPRANextHopType
isisIPRASNPAddress
isisIPRAType
isisRedistributeAddrExistState
isisSummAddrExistState
isisSummAddrFullMetric
isisSummAddrMetric
isisSysL2toL1Leaking

```

7.2.7. Delay Convergence

These attributes can be used to slow convergence by increasing the minimal interval required to update a packet.

```

isisCircLevelCSNPInterval
isisCircLevelLSPThrottle
isisCircLevelMinLSPRetransInt
isisCircLevelPartSNPInterval
isisSysWaitTime
isisCircPassiveCircuit

```

7.2.8. Avoid Detection

By turning off traps, we can prevent a Network Management station from observing problems in the network caused by other aspects of an attack.

```
isisSysNotificationEnable
```

7.2.9. Prevent Updates

Mesh Groups can be used to prevent the transmission of Link State PDUs on certain interfaces, delaying or preventing the propagation of updates.

```

isisCircMeshGroup
isisCircMeshGroupEnabled

```

7.2.10. Hijack LAN

If we have compromised a router, we can use this attribute to become the designated router and lie about the topology of a LAN.

```
isisCircLevelISPRIORITY
```

7.2.11. Create Problems for CLNS Networks

This attribute can be used to modify the handling of CLNS traffic.

```
isisRAAddrPrefix
isisRAAdminState
isisRAExistState
isisRAMapType
isisRAMetric
isisRAMetricType
isisRASNPAAddress
isisRASNPMask
isisRASNPAPrefix
isisRAType
isisSysPollESHelloRate
```

7.2.12. Mostly Harmless

The following writable attributes do not pose a known security risk.

```
isisCircExtDomain
isisCircExtendedCircID
isisCircIfIndex
isisCircLevelHelloMultiplier
isisCircType
```

7.2.13. Recommendations

Much of the MIB is used to set or read attributes which are readily visible to any intruder who has access to traffic. None of the security attributes are setable or visible through the MIB. Read access to the MIB does not pose additional risks or vulnerabilities.

If write access is to be provided, it is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an

instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

8. Normative References

- [ISO10589] ISO 10589, "Intermediate system to Intermediate system routeing information exchange protocol for use in conjunction with the Protocol for providing the Connectionless-mode Network Service (ISO 8473)," ISO/IEC 10589:2002.
- [ISO10733] ISO 10733, "Information Processing Systems - Open Systems Interconnection - Specification of the elements of Management Information related to OSI Network layer Standards", September 1998.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC1195] Callon, R., "Use of OSI IS-IS for routing in TCP/IP and dual environments", RFC 1195, December 1990.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", RFC 3289, May 2002.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, December 2002.
- [RFC2578] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.

[RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.

9. Informative References

[RFC2973] Balay, R., Katz, D., and J. Parker, "IS-IS Mesh Groups", RFC 2973, October 2000.

[RFC3373] Katz, D. and R. Saluja, "Three-Way Handshake for Intermediate System to Intermediate System (IS-IS) Point-to-Point Adjacencies", RFC 3373, September 2002.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

Authors' Address

Jeff Parker
Department of Computer Science
Middlebury College,
Middlebury, Vermont 05753

EMail: jeffp@middlebury.edu

Full Copyright Statement

Copyright (C) The Internet Society (2006).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgement

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).

